
SPECIFICATIONS			
PARAMETERS	AMETERS VALUES		
RATED INPUT POWER	3	W	
MAX INPUT POWER	4	W	
IMPEDANCE	4 ± 15%	OHM	
OUTPUT SPL @ 1W/0.5M	00 + 0	40.4	
(AT 0.6, 0.8, 1.0, 1.2 kHz)	86 ± 3	dBA	
DISTORTION (MAX.)	5%	-	
RESONANT FREQUENCY	180 ± 20%	Hz	
FREQUENCY RANGE	100 ~ 20,000	Hz	
HOUSING MATERIAL	METAL	-	
CONE MATERIAL	PAPER	-	
MAGNET MATERIAL	MATERIAL RARE EARTH		
OPERATING TEMPERATURE -40 ~ +85		°C	
WEIGHT	25	grams	

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

	REVISION HISTORY				
LTR	DESCRIPTION	DATE	APPROVED		
-	RELEASED FROM ENGINEERING	5/4/2010			
Α	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	6/15/2010	B.R.		



AT LEAST 0.8mm
AGM MOVEMENT
AFFLE OPENING)



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	0175	
DIMENSIONS ARE IN MILLIMETERS,	SIZE	
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	A 3	
AS04004PR-R.idw		

5/4/2010	С
DIJI	
Saudio	ว
aaan	
	pul

Checked by

Designed by

Date	Approved by	Date	Drawn Date	
5/4/2010	B.R.	5/4/2010	6/15/2010	
AS04004PR-R				

Speaker Edition Sheet

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PUI Audio:
AS04004PR-R