



**ALPHA & OMEGA
SEMICONDUCTOR**

AON6407

30V P-Channel MOSFET

General Description

The AON6407 combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is ideal for load switch and battery protection applications.


Product Summary

| | |
|------------------------------------|---------|
| V_{DS} | -30 |
| I_D (at $V_{GS} = -10V$) | -85A |
| $R_{DS(ON)}$ (at $V_{GS} = -10V$) | < 4.5mΩ |
| $R_{DS(ON)}$ (at $V_{GS} = -6V$) | < 6.0mΩ |



100% UIS Tested
100% R_g Tested



DFN5X6



Top View



Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

| Parameter | Symbol | Maximum | Units |
|---|----------------|------------|-------|
| Drain-Source Voltage | V_{DS} | -30 | V |
| Gate-Source Voltage | V_{GS} | ± 25 | V |
| Continuous Drain Current ^G | I_D | -85 | A |
| | | -67 | |
| Pulsed Drain Current ^C | I_{DM} | -200 | |
| Continuous Drain Current | I_{DSM} | -32 | A |
| | | -25.5 | |
| Avalanche Current ^C | I_{AS} | 45 | A |
| Avalanche energy $L=0.1mH$ ^C | E_{AS} | 101 | mJ |
| Power Dissipation ^B | P_D | 83 | W |
| | | 33 | |
| Power Dissipation ^A | P_{DSM} | 7.3 | W |
| | | 4.7 | |
| Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | °C |

Thermal Characteristics

| Parameter | Symbol | Typ | Max | Units |
|--|-----------------|-----|-----|-------|
| Maximum Junction-to-Ambient ^A | $R_{\theta JA}$ | 14 | 17 | °C/W |
| | | 40 | 55 | °C/W |
| Maximum Junction-to-Case | $R_{\theta JC}$ | 1.1 | 1.5 | °C/W |

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|-----------------------------|--|--|-------|------|----------|------------------|
| STATIC PARAMETERS | | | | | | |
| BV_{DSS} | Drain-Source Breakdown Voltage | $I_D=-250\mu\text{A}, V_{GS}=0\text{V}$ | -30 | | | V |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS}=-30\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$ | | | -1 | μA |
| I_{GSS} | Gate-Body leakage current | $V_{DS}=0\text{V}, V_{GS}=\pm25\text{V}$ | | | ±100 | nA |
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage | $V_{DS}=V_{GS}, I_D=-250\mu\text{A}$ | -1.6 | -2.1 | -2.6 | V |
| $I_{\text{D(ON)}}$ | On state drain current | $V_{GS}=-10\text{V}, V_{DS}=-5\text{V}$ | -200 | | | A |
| $R_{\text{DS(ON)}}$ | Static Drain-Source On-Resistance | $V_{GS}=-10\text{V}, I_D=-20\text{A}$ $T_J=125^\circ\text{C}$ | 3.3 | 4.5 | | $\text{m}\Omega$ |
| | | $V_{GS}=-6\text{V}, I_D=-20\text{A}$ | 4.4 | 6 | | $\text{m}\Omega$ |
| g_{FS} | Forward Transconductance | $V_{DS}=-5\text{V}, I_D=-20\text{A}$ | 65 | | | S |
| V_{SD} | Diode Forward Voltage | $I_S=-1\text{A}, V_{GS}=0\text{V}$ | -0.69 | -1 | | V |
| I_S | Maximum Body-Diode Continuous Current ^G | | | | -85 | A |
| DYNAMIC PARAMETERS | | | | | | |
| C_{iss} | Input Capacitance | $V_{GS}=0\text{V}, V_{DS}=-15\text{V}, f=1\text{MHz}$ | | 3505 | | pF |
| C_{oss} | Output Capacitance | | | 900 | | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 650 | | pF |
| R_g | Gate resistance | $V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$ | | 4.6 | 9.2 | Ω |
| SWITCHING PARAMETERS | | | | | | |
| $Q_g(10\text{V})$ | Total Gate Charge | $V_{GS}=-10\text{V}, V_{DS}=-15\text{V}, I_D=-20\text{A}$ | | 75 | 105 | nC |
| Q_{gs} | Gate Source Charge | | | 13 | | nC |
| Q_{gd} | Gate Drain Charge | | | 23 | | nC |
| $t_{\text{D(on)}}$ | Turn-On DelayTime | $V_{GS}=-10\text{V}, V_{DS}=-15\text{V}, R_L=0.75\Omega, R_{\text{GEN}}=3\Omega$ | | 14 | | ns |
| t_r | Turn-On Rise Time | | | 16 | | ns |
| $t_{\text{D(off)}}$ | Turn-Off DelayTime | | | 94 | | ns |
| t_f | Turn-Off Fall Time | | | 75 | | ns |
| t_{rr} | Body Diode Reverse Recovery Time | $I_F=-20\text{A}, dI/dt=500\text{A}/\mu\text{s}$ | | 35 | | ns |
| Q_{rr} | Body Diode Reverse Recovery Charge | $I_F=-20\text{A}, dI/dt=500\text{A}/\mu\text{s}$ | | 75 | | nC |

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The Power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C . The value in any given application depends on the user's specific board design, and the maximum temperature of 150°C may be used if the PCB allows it.

B. The power dissipation P_D is based on $T_{J(\text{MAX})}=150^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=150^\circ\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ\text{C}$. Maximum UIS current limited by test equipment.

D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(\text{MAX})}=150^\circ\text{C}$. The SOA curve provides a single pulse rating.

G. The maximum current rating is package limited.

H. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS


Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)
















Figure 6: Body-Diode Characteristics (Note E)



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 12: Single Pulse Avalanche capability (Note C)

Figure 13: Power De-rating (Note F)

Figure 14: Current De-rating (Note F)

Figure 15: Single Pulse Power Rating Junction-to-Ambient (Note H)

Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

