

## Tin Coated Split Point Jobber Drills

**DORMER**



DIN 338/BS 328

### Flute geometry

Right hand spiral and wider flutes

### Point angle

118° special Dormer "P.S. Point" giving higher positional accuracy

### Surface treatment

Tin coated (Titanium Nitride coating)

### Application

High speed steel tin coated jobber drill allows increased cutting speed and improved tool life.

493986

### Metric

Size (mm)	Flute Length (mm)	Overall Length (mm)	Order Code	Price Each
3.00	33	61	138-9516	
3.20	36	65	138-9528	
3.30	36	65	138-9529	
3.40	39	70	138-9530	
3.50	39	70	138-9517	
3.70	39	70	138-9532	
3.80	43	75	138-9533	
4.00	43	75	137-4251	
4.10	43	75	138-9534	
4.20	43	75	138-9535	
4.30	47	80	138-9536	
4.50	47	80	148-5506	
4.90	52	86	137-4257	
5.00	52	86	138-9519	
5.10	52	86	138-9538	
5.20	52	86	138-9539	
5.50	57	93	137-4252	
5.70	57	93	138-9540	
6.00	57	93	137-4253	
6.50	63	101	138-9521	
6.80	69	109	138-9522	
7.00	69	109	138-9523	
7.20	69	109	138-9541	
7.50	69	109	148-5508	
7.70	75	117	138-9542	
8.00	75	117	138-9524	
8.20	75	117	138-9544	
8.50	75	117	138-9525	
8.70	81	125	138-9545	
9.00	81	125	138-9526	
9.50	81	125	148-5509	
10.00	87	133	148-5510	
10.20	87	133	148-5511	
10.50	87	133	137-4255	
11.00	94	142	148-5512	
11.50	94	142	148-5513	
12.00	101	151	138-9527	
12.50	101	151	148-5514	

### Fractional

Size	Flute Length	Overall Length	Order Code	Price Each
1/8"	36mm	65mm	137-4256	