




REVISION R RECOMMENDED BOARD LAYOUT .900 [22.86] 01 .250 [6.35] SEE DETAIL 'B' .025 [0.64] .0100 [.254] TRACE $\emptyset.0310 \ [\emptyset.787]$ FREE OD SOLDER MASK $\emptyset.0200 \ [\ \emptyset.635]$ PAD $\emptyset.0100 \ [\ \emptyset.305]$ DETAIL 'B' VIA (PLATED)

RECOMMENDED STENCIL LAYOUT STENCIL TO BE .0060[0.152] THICK







PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

F:\DWG\MISC\MKTG\ASP-103614-04-MKT.SLDDRW



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

SHEET SCALE: 3:1

VITA 42 (LEAD FREE) SOCKET ASSEMBLY

ASP-103614-04

BY: TAMMY W 09/11/06

SHEET 2 OF 2