

Stackable Aerial Cable Spacer – Weather Resistant Polypropylene



- Designed for use in parallel or perpendicular applications
- For use with Dura-Ty™ Cable Ties shown on the previous page
- Each spacer snaps into another to increase spacer heights by 1/2 inch increments
- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use

Part Number	Length		Width		Height		Used with Cable Ties*	Bulk Pkg. Qty.	Bulk Ctn. Qty.
	In.	mm	In.	mm	In.	mm			
SACS50-T100	2.08	52.8	1.16	29.5	.71	18.0	LH, H, EH	200	2000


*Cable tie cross section sizes: LH = Light-Heavy, H = Heavy, and EH = Extra-Heavy.

Aerial Support Ties – Weather Resistant Polypropylene

- Designed to attach coax or telephone cable to the 1/4 inch (6.4mm) or 5/16 inch (7.9mm) support strand to form the expansion loop and keep equipment and cables clear of pole hardware
- One-piece construction with integral 1/2 inch (12.7mm) spacer reduces inventory costs of separate spacer and bands, and installs faster to lower the installed cost
- Releasable and re-usable
- Hand install only



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N		
AST10-5-C100	5.6	142	.45	11.4	.06	1.4	1.00	25.4	75	334	100	1000
AST15-5-C100	6.9	175	.45	11.4	.06	1.4	1.50	38.1	75	334	100	1000
AST20-5-C100	8.4	214	.45	11.4	.06	1.4	2.00	50.8	75	334	100	1000
AST25-5-C100	10.0	254	.45	11.4	.07	1.8	2.50	63.5	75	334	100	1000



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[AST10-5-C100](#) [AST15-5-C100](#) [AST20-5-C100](#) [AST25-5-C100](#)