
- NOTES: 1.0 MATERIALS:
  - 1.1 HOUSING: STAINLESS STEEL PER ASTM-A582, TYPE 303.
  - 1.2 CENTER CONTACT: BERYLLIUM COPPER ROD ALLOY C172, PER ASTM-B196.
  - 1.3 DIELECTRIC: PTFE FLUOROCARBON PER ASTM-D1457.
- 2.0 PLATING:
- 2.1 HOUSING: PASSIVATED PER MIL-F-14072 AND QQ-P-35.
- 2.2 CENTER CONTACT: GOLD PER MIL-G-45204, TYPE II, CLASS 2.
- 3.0 ELECTRICAL SPECIFICATIONS: 3.1 FREQUENCY RANGE: DC to 18.0 GHz 3.2 VSWR (MAX.): DC to 4.0 GHz: 1.04:1 4.0 TO 8.0 GHz; 1.07:1 8.0 to 18.0 GHz: 1.12:1 3.3 IMPEDANCE: 50 OHMS
- 4.0 MARKING: MARK UNIT AS SHOWN (REF: INK-02669-27-28)
- 5.0 DIMENSIONS IN PARENTHESIS ARE IN MILLIMETERS.

- TYPE N JACK PER MIL-PRF-39012		3.5mm JACK
	T-2715-NF- ADAPTER	
	— 1.50(38.1) —	<b>Ba</b> re

UNLESS OTHERWISE NOTED DIMENSIONS	55cm NO. 34078	MIDW	<b>EST</b>	MIC	'ROW.	AVE
ARE IN INCHES AND TOLERANCES ARE:	NOTICE: The contained ir	information	TITLE			
3 PLACE DECIMALS ±.005	drawing is			ADAPTEI	R	
2 PLACE DECIMALS ±.02	and must n		3.5mm	JACK t	o TYPE	N JACK
FRACTIONS ±1/64	without the of Midwest					
PARALLELITY: T.I.R					Academic 1997	
FLATNESS: T.I.R.	DRAWN/DATE M.HOLLMAN 12/15/92		drawing nui ADT-27		MF-02	
CONCENTRICITY: T.I.R		APPROVED/DATE				
ANGLES AND PERPENDICULARITY: ±1*	A.BEATTY 12/18/92		SCALE:	3=1	sheet 1	of 1

אב י	DESCRIPTION	UAIE
ł	RELEASED	3/3/83
А	ECR 2805	4/19/84
в	ECR 6545	7/25/89
81	UPDATE MODEL #	12/14/92
υ	UPDATE ON CAD	12/16/92
сı	ADDED TITLEBLOCK	3/16/05





## DWG. NO. WAS: 04560-01-00

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: ADT-2715-NF-3MF-02