

Microwave MLC's

AQ Series

AVX RF




These porcelain and ceramic dielectric multilayer capacitor (MLC) chips are best suited for RF/ Microwave applications typically ranging from 10 MHz to 4.2 GHz. Characteristic is a fine grained, high density, high purity dielectric material impervious to moisture with heavy internal palladium electrodes.

These characteristics lend well to applications requiring:

- 1) high current carrying capabilities;
- 2) high quality factors;
- 3) very low equivalent series resistance;
- 4) very high series resonance;
- 5) excellent stability under stresses of changing voltage, frequency, time and temperature.

MECHANICAL DIMENSIONS: inches (millimeters)



Case	Length (L)	Width (W)	Thickness (T)	Band Width (bw)
AQ11	.055±.015 (1.40±.381)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 + .010 -.005 (.254 +.254 -.127)
AQ12	.055 + .015 - .010 (1.40+ .381 - .254)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 + .010 -.005 (.254 +.254 -.127)
AQ13	.110±.020 (2.79±.508)	.110±.020 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)
AQ14	.110 + .020 - .010 (2.79 +.889 -.254)	.110±.010 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)

HOW TO ORDER

AQ	11	E	M	100	J	A	1	ME
AVX Style AQ11, AQ12, AQ13, AQ14	Case Size (See Chart)	Voltage Code 5 = 50V 1 = 100V E = 150V 2 = 200V 9 = 300V 7 = 500V	Temperature Coefficient Code M = +90±20ppm/°C (AQ11/12/13/14) A = 0±30ppm/°C (AQ11/12/13/14) C = 15% ("J" Termination only) (AQ12/14)	Capacitance EIA Capacitance Code in pF. First two digits = significant figures or "R" for decimal place. Third digit = number of zeros or after "R" significant figures.	Capacitance Tolerance Code B = ±.1 pF C = ±.25 pF D = ±.5 pF F = ±1% G = ±2% J = ±5% K = ±10% M = ±20% N = ±30%	Failure Rate Code A = Not Applicable	Termination Style Code 1 = Pd/Ag (AQ11/13 only) 7 = Ag/Ni/Au (AQ11/13 only) J = Nickel Barrier Sn/Pb (60/40) - (AQ12/14 only) T = 100% Tin (AQ12/14 only)	Packaging* Code 3A = 13" Reel Unmarked ME = 7" Reel Marked RE = 13" Reel Marked WE = Waffle Pack Marked BE = Bulk Marked

PACKAGING

Standard Packaging = Waffle Pack (maximum quantity is 80)

Not RoHS Compliant

TAPE & REEL: All tape and reel specifications are in compliance with EIA RS481 (equivalent to IEC 286 part 3).

Sizes SQCA through SQCB, CDR11/12 through 13/14.

—8mm carrier
—7" reel: ≤0.040" thickness = 2000 pcs
 ≤0.075" thickness = 2000 pcs
—13" reel: ≤0.075" thickness = 10,000 pcs



For RoHS compliant products,
please select correct termination style.

Microwave MLC's

AQ Series



ELECTRICAL SPECIFICATIONS

AQ11, AQ12, AQ13, AQ14		
	M & A	C
Temperature Coefficient (TCC)	(M) +90 ± 20 PPM/°C (-55°C to +125°C) (M) +90 ± 30 PPM/°C (+125°C to +175°C) (A) 0 ± 30 PPM/°C	±15% (-55°C to 125°C)
Capacitance Range	(M) 0.1 pF to 1000 pF (A) 0.1 pF to 5100 pF	0.001µF to 0.1µF
Operating Temperature	0.1 pF to 330 pF: from -55°C to +175°C 360 pF to 5100 pF: from -55°C to +125°C	-55°C to +125°C
Quality Factor (Q)	M Dielectric A & B Case	Greater than 10,000 at 1 MHz
	A Dielectric B Case	Greater than 10,000 at 1 MHz Greater than 2,000 at 1 MHz Greater than 2,000 at 1 KHz
	A Dielectric A Case	Greater than 10,000 at 1 MHz Greater than 2,000 at 1 MHz
Insulation Resistance (IR)	0.1 pF to 470 pF 10 ⁶ Megohms min. @ 25°C at rated WVDC 10 ⁵ Megohms min. @ 125°C at rated WVDC 510 pF to 5100 pF 10 ⁵ Megohms min. @ 25°C at rated WVDC 10 ⁴ Megohms min. @ 125°C at rated WVDC	10 ⁴ Megohms min. @ 25°C at rated WVDC 10 ³ Megohms min. @ 125°C at rated WVDC
Working Voltage (WVDC)	See Capacitance Values table	See Capacitance Values table
Dielectric Withstanding Voltage (DWV)	250% of rated WVDC for 5 secs (for 500V rated 150% of rated voltage)	250% of rated WVDC for 5 secs
Aging Effects	None	<3% per decade hour
Piezoelectric Effects	None	None
Capacitance Drift	± (0.02% or 0.02 pF), whichever is greater	Not Applicable

ENVIRONMENTAL CHARACTERISTICS

AVX SQLB will meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123

Thermal Shock	Mil-STD-202, Method 107, Condition A
Moisture Resistance	Mil-STD-202, Method 106
Low Voltage Humidity	Mil-STD-202, Method 103, condition A, with 1.5 VDC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours
Life Test	Mil-STD-202, Method 108, for 2000 hours at 125°C
Shock	Mil-STD-202, Method 213, Condition J
Vibration	Mil-STD-202, Method 204, Condition B
Immersion	Mil-STD-202, Method 104, Condition B
Salt Spray	Mil-STD-202, Method 101, Condition B
Solderability	Mil-STD-202, Method 208
Terminal Strength	Mil-STD-202, Method 211
Temperature Cycling	Mil-STD-202, Method 102, Condition C
Barometric Pressure	Mil-STD-202, Method 105, Condition B
Resistance to Solder Heat	Mil-STD-202, Method 210, Condition C

Microwave MLC's



AQ Series Available Capacitance/Size/WVDC/T.C.

TABLE I: TC: M (+90±20PPM/°C)

CASE SIZE 11, 12, 13 & 14

DIMENSIONS: inches (millimeters)

Case	Length	Width	Thickness	Band Width	Avail. Term.
11	.055±.015 (1.40±.381)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 +.010 -.005 (.254+.254-.127)	1 & 7
12	.055±.025 (1.40±.635)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 +.010 -.005 (.254+.254-.127)	J
13	.110±.020 (2.79±.508)	.110±.020 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)	1 & 7
14	.110 +0.035 -0.020 (2.79 +.889 -.508)	.110±.020 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)	J

Case: AQ11, AQ12

Cap. pF	Cap. Tol.	WVDC
0.1	B	150
0.2	B	150
0.3	B,C	150
0.4	B,C	150
0.5	B, C, D	150
0.6	B, C, D	150
0.7	B, C, D	150
0.8	B, C, D	150
0.9	B, C, D	150
1.0	B, C, D	150
1.1	B, C, D	150
1.2	B, C, D	150
1.3	B, C, D	150
1.4	B, C, D	150
1.5	B, C, D	150
1.6	B, C, D	150
1.7	B, C, D	150
1.8	B, C, D	150
1.9	B, C, D	150
2.0	B, C, D	150
2.2	B, C, D	150
2.4	B, C, D	150
2.7	B, C, D	150
3.0	B, C, D	150
3.3	B, C, D	150
3.6	B, C, D	150
3.9	B, C, D	150
4.3	B, C, D	150
4.7	B, C, D	150
5.1	B, C, D	150
5.6	B, C, D	150
6.2	B, C, D	150
6.8	B, C, J, K, M	150
7.5	B, C, J, K, M	150
8.2	B, C, J, K, M	150
9.1	B, C, J, K, M	150
10	F, G, J, K, M	150
11	F, G, J, K, M	150
12	F, G, J, K, M	150
13	F, G, J, K, M	150
15	F, G, J, K, M	150
16	F, G, J, K, M	150
18	F, G, J, K, M	150
20	F, G, J, K, M	150
22	F, G, J, K, M	150
24	F, G, J, K, M	150
27	F, G, J, K, M	150
30	F, G, J, K, M	150
33	F, G, J, K, M	150
36	F, G, J, K, M	150
39	F, G, J, K, M	150
43	F, G, J, K, M	150
47	F, G, J, K, M	150
51	F, G, J, K, M	150
56	F, G, J, K, M	150
62	F, G, J, K, M	150
68	F, G, J, K, M	150
75	F, G, J, K, M	150
82	F, G, J, K, M	150
91	F, G, J, K, M	150
100	F, G, J, K, M	150

Case: AQ13, AQ14

Cap. pF	Cap. Tol.	WVDC	Cap. pF	Cap. Tol.	WVDC
0.1	B	500	100	F, G, J, K, M	500
0.2	B	500	110	F, G, J, K, M	300
0.3	B,C	500	120	F, G, J, K, M	300
0.4	B,C	500	130	F, G, J, K, M	300
0.5	B, C, D	500	150	F, G, J, K, M	300
0.6	B, C, D	500	160	F, G, J, K, M	300
0.7	B, C, D	500	180	F, G, J, K, M	300
0.8	B, C, D	500	200	F, G, J, K, M	300
0.9	B, C, D	500	220	F, G, J, K, M	200
1.0	B, C, D	500	240	F, G, J, K, M	200
1.1	B, C, D	500	270	F, G, J, K, M	200
1.2	B, C, D	500	300	F, G, J, K, M	200
1.3	B, C, D	500	330	F, G, J, K, M	200
1.4	B, C, D	500	360	F, G, J, K, M	200
1.5	B, C, D	500	390	F, G, J, K, M	200
1.6	B, C, D	500	430	F, G, J, K, M	200
1.7	B, C, D	500	470	F, G, J, K, M	200
1.8	B, C, D	500	510	F, G, J, K, M	150
1.9	B, C, D	500	560	F, G, J, K, M	150
2.0	B, C, D	500	620	F, G, J, K, M	150
2.2	B, C, D	500	680	F, G, J, K, M	150
2.4	B, C, D	500	750	F, G, J, K, M	150
2.7	B, C, D	500	820	F, G, J, K, M	150
3.0	B, C, D	500	910	F, G, J, K, M	150
3.3	B, C, D	500	1000	F, G, J, K, M	150
3.6	B, C, D	500			
3.9	B, C, D	500			
4.3	B, C, D	500			
4.7	B, C, D	500			
5.1	B, C, D	500			
5.6	B, C, D	500			
6.2	B, C, D	500			
6.8	B, C, J, K, M	500			
7.5	B, C, J, K, M	500			
8.2	B, C, J, K, M	500			
9.1	B, C, J, K, M	500			
10	F, G, J, K, M	500			
11	F, G, J, K, M	500			
12	F, G, J, K, M	500			
13	F, G, J, K, M	500			
15	F, G, J, K, M	500			
16	F, G, J, K, M	500			
18	F, G, J, K, M	500			
20	F, G, J, K, M	500			
22	F, G, J, K, M	500			
24	F, G, J, K, M	500			
27	F, G, J, K, M	500			
30	F, G, J, K, M	500			
33	F, G, J, K, M	500			
36	F, G, J, K, M	500			
39	F, G, J, K, M	500			
43	F, G, J, K, M	500			
47	F, G, J, K, M	500			
51	F, G, J, K, M	500			
56	F, G, J, K, M	500			
62	F, G, J, K, M	500			
68	F, G, J, K, M	500			
75	F, G, J, K, M	500			
82	F, G, J, K, M	500			
91	F, G, J, K, M	500			

Microwave MLC's

AVX RF

AQ Series Available Capacitance/Size/WVDC/T.C.

TABLE II: TC: A (0±30PPM/°C)

CASE SIZE 11, 12, 13 & 14

DIMENSIONS: inches (millimeters)

Case	Length	Width	Thickness	Band Width	Avail. Term.
11	.055±.015 (1.40±.381)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 +.010 -.005 (.254+.254 -.127)	1 & 7
12	.055±.025 (1.40±.635)	.055±.015 (1.40±.381)	.020/.057 (.508/1.45)	.010 +.010 -.005 (.254+.254 -.127)	J
13	.110±.020 (2.79±.508)	.110±.020 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)	1 & 7
14	.110 +0.035 -0.020 (2.79 +.889 -.508)	.110±.020 (2.79±.508)	.030/.102 (.762/2.59)	.015±.010 (.381±.254)	J

Case: AQ11, AQ12					
Cap. pF	Cap. Tol.	WVDC	Cap. pF	Cap. Tol.	WVDC
0.1	B	150	24	F, G, J, K, M	150
0.2	B	150	27	F, G, J, K, M	150
0.3	B,C	150	30	F, G, J, K, M	150
0.4	B,C	150	33	F, G, J, K, M	150
0.5	B, C, D	150	36	F, G, J, K, M	150
0.6	B, C, D	150	39	F, G, J, K, M	150
0.7	B, C, D	150	43	F, G, J, K, M	150
0.8	B, C, D	150	47	F, G, J, K, M	150
0.9	B, C, D	150	51	F, G, J, K, M	150
1.0	B, C, D	150	56	F, G, J, K, M	150
1.1	B, C, D	150	62	F, G, J, K, M	150
1.2	B, C, D	150	68	F, G, J, K, M	150
1.3	B, C, D	150	75	F, G, J, K, M	150
1.4	B, C, D	150	82	F, G, J, K, M	150
1.5	B, C, D	150	91	F, G, J, K, M	150
1.6	B, C, D	150	100	F, G, J, K, M	150
1.7	B, C, D	150	110	F, G, J, K, M	50
1.8	B, C, D	150	120	F, G, J, K, M	50
1.9	B, C, D	150	130	F, G, J, K, M	50
2.0	B, C, D	150	150	F, G, J, K, M	50
2.2	B, C, D	150	160	F, G, J, K, M	50
2.4	B, C, D	150	180	F, G, J, K, M	50
2.7	B, C, D	150	200	F, G, J, K, M	50
3.0	B, C, D	150	220	F, G, J, K, M	50
3.3	B, C, D	150	240	F, G, J, K, M	50
3.6	B, C, D	150	270	F, G, J, K, M	50
3.9	B, C, D	150	300	F, G, J, K, M	50
4.3	B, C, D	150	330	F, G, J, K, M	50
4.7	B, C, D	150	360	F, G, J, K, M	50
5.1	B, C, D	150	390	F, G, J, K, M	50
5.6	B, C, D	150	430	F, G, J, K, M	50
6.2	B, C, D	150	470	F, G, J, K, M	50
6.8	B, C, J, K, M	150	510	F, G, J, K, M	50
7.5	B, C, J, K, M	150	560	F, G, J, K, M	50
8.2	B, C, J, K, M	150	620	F, G, J, K, M	50
9.1	B, C, J, K, M	150	680	F, G, J, K, M	50
10	F, G, J, K, M	150	750	F, G, J, K, M	50
11	F, G, J, K, M	150	820	F, G, J, K, M	50
12	F, G, J, K, M	150	910	F, G, J, K, M	50
13	F, G, J, K, M	150	1000	F, G, J, K, M	50
15	F, G, J, K, M	150			
16	F, G, J, K, M	150			
18	F, G, J, K, M	150			
20	F, G, J, K, M	150			
22	F, G, J, K, M	150			

Case: AQ13, AQ14					
Cap. pF	Cap. Tol.	WVDC	Cap. pF	Cap. Tol.	WVDC
0.1	B	500	51	F, G, J, K, M	500
0.2	B	500	56	F, G, J, K, M	500
0.3	B,C	500	62	F, G, J, K, M	500
0.4	B,C	500	68	F, G, J, K, M	500
0.5	B, C, D	500	75	F, G, J, K, M	500
0.6	B, C, D	500	82	F, G, J, K, M	500
0.7	B, C, D	500	91	F, G, J, K, M	500
0.8	B, C, D	500	100	F, G, J, K, M	500
0.9	B, C, D	500	110	F, G, J, K, M	300
1.0	B, C, D	500	120	F, G, J, K, M	300
1.1	B, C, D	500	130	F, G, J, K, M	300
1.2	B, C, D	500	150	F, G, J, K, M	300
1.3	B, C, D	500	160	F, G, J, K, M	300
1.4	B, C, D	500	180	F, G, J, K, M	300
1.5	B, C, D	500	200	F, G, J, K, M	200
1.6	B, C, D	500	220	F, G, J, K, M	200
1.7	B, C, D	500	240	F, G, J, K, M	200
1.8	B, C, D	500	270	F, G, J, K, M	200
1.9	B, C, D	500	300	F, G, J, K, M	200
2.0	B, C, D	500	330	F, G, J, K, M	200
2.2	B, C, D	500	360	F, G, J, K, M	200
2.4	B, C, D	500	390	F, G, J, K, M	200
2.7	B, C, D	500	430	F, G, J, K, M	200
3.0	B, C, D	500	470	F, G, J, K, M	200
3.3	B, C, D	500	510	F, G, J, K, M	150
3.6	B, C, D	500	560	F, G, J, K, M	150
3.9	B, C, D	500	620	F, G, J, K, M	150
4.3	B, C, D	500	680	F, G, J, K, M	150
4.7	B, C, D	500	750	F, G, J, K, M	150
5.1	B, C, D	500	820	F, G, J, K, M	150
5.6	B, C, D	500	910	F, G, J, K, M	150
6.2	B, C, D	500	1000	F, G, J, K, M	150
6.8	B, C, J, K, M	500	1100	F, G, J, K, M	50
7.5	B, C, J, K, M	500	1200	F, G, J, K, M	50
8.2	B, C, J, K, M	500	1300	F, G, J, K, M	50
9.1	B, C, J, K, M	500	1500	F, G, J, K, M	50
10	F, G, J, K, M	500	1600	F, G, J, K, M	50
11	F, G, J, K, M	500	1800	F, G, J, K, M	50
12	F, G, J, K, M	500	2000	F, G, J, K, M	50
13	F, G, J, K, M	500	2200	F, G, J, K, M	50
15	F, G, J, K, M	500	2400	F, G, J, K, M	50
16	F, G, J, K, M	500	2700	F, G, J, K, M	50
18	F, G, J, K, M	500	3000	F, G, J, K, M	50
20	F, G, J, K, M	500	3300	F, G, J, K, M	50
22	F, G, J, K, M	500	3600	F, G, J, K, M	50
24	F, G, J, K, M	500	3900	F, G, J, K, M	50
27	F, G, J, K, M	500	4300	F, G, J, K, M	50
30	F, G, J, K, M	500	4700	F, G, J, K, M	50
33	F, G, J, K, M	500	5000	F, G, J, K, M	50
36	F, G, J, K, M	500	5100	F, G, J, K, M	50
39	F, G, J, K, M	500			
43	F, G, J, K, M	500			
47	F, G, J, K, M	500			

TABLE III: TC: C (±15%) CASE SIZE 12 & 14

Case: AQ12				Case: AQ14				
Cap. pF	Cap. Tol.	WVDC	Cap. pF	Cap. Tol.	WVDC	Cap. pF	Cap. Tol.	WVDC
1000	K, M, N	50	2200	K, M, N	50	5100	K, M, N	50
1200	K, M, N	50	2700	K, M, N	50	5600	K, M, N	50
1500	K, M, N	50	3300	K, M, N	50	6800	K, M, N	50
1800	K, M, N	50	3900	K, M, N	50	8200	K, M, N	50
2000	K, M, N	50	4700	K, M, N	50	10000	K, M, N	50
						12000	K, M, N	50
						15000	K, M, N	50
						18000	K, M, N	50
						27000	K, M, N	50
						33000	K, M, N	50
						39000	K, M, N	50
						47000	K, M, N	50
						68000	K, M, N	50
						82000	K, M, N	50
						100000	K, M, N	50

AVX

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AVX:

[AQ11EA180FA1ME](#) [AQ11EA180GA1ME](#) [AQ11EA220FA1ME](#) [AQ11EA220GA1ME](#) [AQ11EA220JA1ME](#)
[AQ11EA270FA1ME](#) [AQ11EA270GA1ME](#) [AQ11EA330GA1ME](#) [AQ11EA390GA1ME](#) [AQ11EA470FA1ME](#)
[AQ11EA470JA1ME](#) [AQ11EA560GA1ME](#) [AQ11EA680GA1ME](#) [AQ11EA101JA1ME](#) [AQ11EA120FA1ME](#)
[AQ11EA120GA1ME](#) [AQ11EA150FA1ME](#) [AQ11EA150GA1ME](#) [AQ137A330FA1ME](#) [AQ137A330JA1ME](#)
[AQ137A560FA1ME](#) [AQ139A151FA1ME](#) [AQ139A181GA1ME](#) [AQ137A101JA1ME](#) [AQ137A150FA1ME](#)
[AQ137A180GA1ME](#) [AQ137A270FA1ME](#) [AQ137A270GA1ME](#) [AQ137A270JA1ME](#) [AQ137M270JA1ME](#)
[AQ13EA102FA1WE](#) [AQ145M102JAJME](#) [AQ135M821JA1ME](#) [AQ13EM621JA1BE](#) [AQ065M120GAJ3A](#)
[AQ135M821JA1BE](#) [AQ065M470GAJ3A](#) [AQ135M911JA1BE](#) [AQ065M1R5BAJ1A](#) [AQ135M911JA1ME](#)
[AQ145M102JAJBE](#) [AQ137M5R1DA7WE](#) [AQ11EM0R9CA1ME](#) [AQ135M751JA1BE](#) [AQ147M1R1CAJWE](#)
[AQ147M1R1CAJME](#) [AQ147M5R1CAJME](#) [AQ147M5R1CAJWE](#) [AQ147M5R1CAJBE](#) [AQ147M9R1CAJWE](#)
[AQ147M9R1CAJME](#) [AQ137M5R6CA1BE](#) [AQ11EA510GA1WE](#) [AQ147A4R7CAJWE](#) [AQ11EM1R2CA1WE](#)
[AQ06EM0R8BAJ1A](#) [AQ06EM1R8BAJ1A](#) [AQ147M4R7CAJWE](#) [AQ06EM6R8BAJ1A](#) [AQ147M2R7CAJBE](#)
[AQ06EM1R8BAJ6A](#) [AQ149M111FAJRE](#) [AQ149M121FAJME](#) [AQ147M0R7CAJWE](#) [AQ149A111FAJME](#)
[AQ06EM0R8BAJ6A](#) [AQ149M111FAJME](#) [AQ149M131FAJME](#) [AQ149M161FAJME](#) [AQ149M151FAJBE](#)
[AQ149A151FAJME](#) [AQ149M131FAJBE](#) [AQ147M2R7CAJWE](#) [AQ11EA510GA1ME](#) [AQ147A2R7CAJWE](#)
[AQ147M4R7CAJBE](#) [AQ149A121FAJME](#) [AQ125M3R3DAJME](#) [AQ137M101FA7ME](#) [AQ12EM9R1JAJME](#)
[AQ12EM0R7BAJME](#) [AQ14EM102KHJWE](#) [AQ137M3R3CA1ME](#) [AQ12EM1R7BAJME](#) [AQ12EM2R7BAJME](#)
[AQ141A511FAJWE](#) [AQ12EM4R7BAJBE](#) [AQ137M6R8CA7ME](#) [AQ12EA1R7BAJME](#) [AQ12EM9R1JAJWE](#)
[AQ12EM2R7BAJBE](#) [AQ12EA2R7BAJME](#) [AQ14EM1R5BAJME](#) [AQ12EM4R7BAJME](#) [AQ06EM510KAJ6A](#)
[AQ06VA3R3BAJ1A](#) [AQ147M180GAJME](#) [AQ147M390GAJME](#) [AQ147M680GAJME](#) [AQ12EM9R1CAJWE](#)