


Angular Ground / Earth Spring Clamp

Besides having angular wire entry, these Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with DIN rails. They are green / yellow color coded as per industry standards.



Terminal Width	5 mm	8 mm	5 mm
Height x Length	42 x 54 mm	48 x 74 mm	42 x 54 mm
Stripping Length	11 mm	15 mm	12 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 spring clamp connection, grounding through alloy feet	2 spring clamp connection, grounding through alloy feet	3 spring clamp connection, grounding through alloy feet
Approvals			
Wire Range	0.34-2.5 sq.mm. 22-12 AWG	0.2-6 sq.mm. 22-8 AWG	0.34-2.5 sq.mm. 22-12 AWG
Voltage Rating		800V	800V
Current Rating		41A	24A
Other Approvals			

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	AGT2.5	100	AGT6	50	AGT2.5/3	100
End Plate	EPAS2.5	50	EPAS6	50	EPAS2.5	50
DIN Rail for ordering information refer to pages 90-91						
Marking Tags	MT5	100	MT8	100	MT5	100

AGT2.5/4		AGT4		AGT4/3		AGT4/4		AGT6/3	
									
5 mm		6 mm		6 mm		6 mm		8 mm	
42 x 54 mm		42 x 61.5 mm		42 x 61.5 mm		42 x 61.5 mm		48 x 74 mm	
12 mm		15 mm		15 mm		15 mm		15 mm	
Polyamide 6.6		Polyamide 6.6		Polyamide 6.6		Polyamide 6.6		Polyamide 6.6	
4 spring clamp connection, grounding through alloy feet		2 spring clamp connection, grounding through alloy feet		3 spring clamp connection, grounding through alloy feet		4 spring clamp connection, grounding through alloy feet		3 spring clamp connection, grounding through alloy feet	
									
22-12 AWG	0.34-2.5 sq.mm.	22-12 AWG	0.2-4 sq.mm.	22-10 AWG	0.2-4 sq.mm.	22-10 AWG	0.2-4 sq.mm.	22-10 AWG	0.2-6 sq.mm.
800V					800V		800V		800 V
24A					32A		32A		41 A
									
Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
AGT2.5/4	100	AGT4	100	AGT4/3	50	AGT4/4	50	AGT6/3	50
EPAS2.5	50	EPAS4	50	EPAS4	50	EPAS4	50	EPAS6	50
									
MT5	100	MT6	100	MT6	100	MT6	100	MT8	100