

RoHS compliant

FEATURES

- Excellent high frequency characteristics (to 2.6GHz)

Type	Frequency	900MHz	2.6GHz
Impedance 50Ω	V.S.W.R. (Max.)	1.3	1.7
	Insertion loss (dB, Max.)	0.2	0.7
	Isolation (dB, Min.)	60	30
Impedance 75Ω	V.S.W.R. (Max.)	1.2	1.5
	Insertion loss (dB, Max.)	0.2	0.5
	Isolation (dB, Min.)	60	30

- Surface-mount type also available
- Compact and slim size

Size: 20.2(L) × 11.2(W) × 8.9(H)* mm
.795(L) × .441(W) × .350(H) inch

*The height of Surface-mount type is 9.6 mm .378 inch size.

TYPICAL APPLICATIONS

1. Broadcasting and video markets.

- Digital broadcasting market
- STB/tuner market, etc.

2. Communications market

- Antennae switching
- All types of wireless devices

If you wish to use in applications with low level loads or with high frequency switching, please consult us.

ORDERING INFORMATION

RE relays	ARE	1					
Contact arrangement 1: 1 Form C							
Operating function 0: Single side stable type (Impedance 50Ω) 3: Single side stable type (Impedance 75Ω)							
Terminal shape Nil: Standard PC board terminal A: Surface-mount terminal							
Coil voltage (DC) 03: 3V, 4H: 4.5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V (H=0.5)							
Packing style Nil: Carton packing (Standard PC board terminal only) Tube packing (Surface-mount terminal only) Z: Tape and reel packing (picked from 14 pin side)							

TYPES

1. Standard PC board terminal

Nominal coil voltage	Part No.	
	Single side stable type (Impedance 50Ω)	Single side stable type (Impedance 75Ω)
3 V DC	ARE1003	ARE1303
4.5V DC	ARE104H	ARE134H
6 V DC	ARE1006	ARE1306
9 V DC	ARE1009	ARE1309
12 V DC	ARE1012	ARE1312
24 V DC	ARE1024	ARE1324

Standard packing: 50 pcs. in an inner package; 500 pcs. in an outer package

2. Surface-mount terminal

1) Tube package

Nominal coil voltage	Part No.	
	Single side stable type (Impedance 50Ω)	Single side stable type (Impedance 75Ω)
3 V DC	ARE10A03	ARE13A03
4.5V DC	ARE10A4H	ARE13A4H
6 V DC	ARE10A06	ARE13A06
9 V DC	ARE10A09	ARE13A09
12 V DC	ARE10A12	ARE13A12
24 V DC	ARE10A24	ARE13A24

Standard packing: 25 pcs. in an inner package (tube); 200 pcs. in an outer package

2) Tape and reel package

Nominal coil voltage	Part No.	
	Single side stable type (Impedance 50Ω)	Single side stable type (Impedance 75Ω)
3 V DC	ARE10A03Z	ARE13A03Z
4.5V DC	ARE10A4HZ	ARE13A4HZ
6 V DC	ARE10A06Z	ARE13A06Z
9 V DC	ARE10A09Z	ARE13A09Z
12 V DC	ARE10A12Z	ARE13A12Z
24 V DC	ARE10A24Z	ARE13A24Z

Standard packing: 400 pcs. in an inner package (tape and reel); 800 pcs. in an outer package

RATING

1. Coil data

Nominal coil voltage	Pick-up voltage (at 20°C 68°F)	Drop-out voltage (at 20°C 68°F)	Nominal operating current [±10%] (at 20°C 68°F)	Coil resistance [±10%] (at 20°C 68°F)	Nominal operating power	Max. applied voltage (at 70°C 158°F)
3 V DC	75%V or less of nominal voltage (Initial)	10%V or more of nominal voltage (Initial)	66.7mA	45Ω	200mW	110%V of nominal voltage
4.5V DC			44.4mA	101Ω		
6 V DC			33.3mA	180Ω		
9 V DC			22.2mA	405Ω		
12 V DC			16.7mA	720Ω		
24 V DC			8.3mA	2,880Ω		

RE (ARE)

2. Specifications


Characteristics	Item		Specifications
Contact	Arrangement		1 Form C
	Contact material		Gold plating
	Initial contact resistance, max.		Max. 100mΩ (By voltage drop 10V AC 10mA)
Rating	Contact rating		1W (at 2.6 GHz [Impedance 75Ω, V.S.W.R. Max.1.5] [Impedance 50Ω, V.S.W.R. Max.1.7]) 10mA 24V DC (resistive load)
	Contact carrying power		10W (at 2.6GHz [Impedance 75Ω, V.S.W.R. Max.1.5] [Impedance 50Ω, V.S.W.R. Max.1.7])
	Max. switching voltage		30V DC
	Max. switching current		0.5A DC
	Nominal operating power		200mW
High frequency characteristics (Initial) (Impedance 75Ω)	V.S.W.R.		Max. 1.2 (to 900MHz), Max. 1.5 (to 2.6GHz)
	Insertion loss		Max. 0.2dB (to 900MHz), Max. 0.5dB (to 2.6GHz)
	Isolation		Min. 60dB (to 900MHz), Min. 30dB (to 2.6GHz)
High frequency characteristics (Initial) (Impedance 50Ω)	V.S.W.R.		Max. 1.3 (to 900MHz), Max. 1.7 (to 2.6GHz)
	Insertion loss		Max. 0.2dB (to 900MHz), Max. 0.7dB (to 2.6GHz)
	Isolation		Min. 60dB (to 900MHz), Min. 30dB (to 2.6GHz)
Electrical characteristics	Insulation resistance (Initial)		Min. 100MΩ (at 500V DC) Measurement at same location as "Initial breakdown voltage" section.
	Breakdown voltage (Initial)	Between open contacts	500 Vrms for 1min. (Detection current: 10mA)
		Between contact and coil	1,000 Vrms for 1min. (Detection current: 10mA)
		Between contact and earth terminal	500 Vrms for 1min. (Detection current: 10mA)
	Temperature rise (at 20°C)		Max. 60°C (By resistive method, nominal voltage applied to the coil: Contact carrying power: 10W, at 2.6GHz, [Impedance 75Ω, V.S.W.R. ≤ 1.5] [Impedance 50Ω, V.S.W.R. ≤ 1.7])
	Operate time (at 20°C)		Max. 10ms (Nominal operating voltage applied to the coil, excluding contact bounce time.)
Mechanical characteristics	Release time (at 20°C)		Max. 5ms (Nominal operating voltage applied to the coil, excluding contact bounce time.) (without diode)
	Shock resistance	Functional	Min. 500 m/s ² {50 G} (Half-wave pulse of sine wave: 11ms; detection time: 10μs.)
		Destructive	Min. 1,000m/s ² {100 G} (Half-wave pulse of sine wave: 6ms.)
	Vibration resistance	Functional	10 to 55 Hz at double amplitude of 3mm (Detection time: 10μs.)
		Destructive	10 to 55 Hz at double amplitude of 5mm
Expected life	Mechanical		Min. 10 ⁶ (at 180 cpm)
	Electrical		Min. 3×10 ⁵ (1W, 2.6GHz, [Impedance 75Ω, V.S.W.R. ≤ 1.5] [Impedance 50Ω, V.S.W.R. ≤ 1.7]) Min. 3×10 ⁵ (10mA 24V DC (resistive load) (at 20cpm))
Conditions	Conditions for operation, transport and storage*		Ambient temperature: -40°C to +70°C -40°F to +158°F Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature)
Unit weight			Approx. 5 g .18 oz

Note: * The upper operation ambient temperature limit is the maximum temperature that can satisfy the coil temperature rise value. Refer to [6] AMBIENT ENVIRONMENT in GENERAL APPLICATION GUIDELINES.


REFERENCE DATA

1-(1). High frequency characteristics (Impedance 50Ω) (Standard PC board terminal)


• V.S.W.R. characteristics



• Insertion loss characteristics




• Isolation characteristics




1-(2). High frequency characteristics (Impedance 75Ω) (Standard PC board terminal)


- V.S.W.R. characteristics



- Insertion loss characteristics




- Isolation characteristics



DIMENSIONS (mm inch)


The CAD data of the products with a **CAD Data** mark can be downloaded from: <http://industrial.panasonic.com/ac/e/>

1. Standard PC board terminal (50Ω, 75Ω type)

CAD Data

General tolerance: $\pm 0.3 \pm .012$


Schematic (Bottom view)



(Deenergized condition)


2. Surface mount terminal

- 50Ω type


CAD Data

General tolerance: $\pm 0.3 \pm .012$

Schematic (Top view)



(Deenergized condition)

CAD Data

Note: Please consult us regarding recommended PC board patterns.

A: Surface of PC board where relay is mounted.

Technical drawing of a wheel and axle assembly. The wheel has a diameter of 21^{+0.8} dia. (827^{+0.2} dia.). The axle has a diameter of 13^{+0.2} dia. (512^{+0.05} dia.). The wheel has a maximum width of 95 (3,740). The axle has a maximum width of 51.7 (2,035). The wheel has a maximum thickness of 2.0^{+0.5} (79^{+0.5}). The axle has a maximum thickness of 45.5^{+0.2} (1,791^{+0.2}). The wheel has a maximum width of 390^{+0.2} (14,961^{+0.05}).

The plastic becomes brittle if the relay is exposed to a low temperature, low humidity environment for long periods of time.

For general cautions for use, please refer to the “General Application Guidelines”.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[ARE13A12](#) [ARE1003](#) [ARE1006](#) [ARE1009](#) [ARE1012](#) [ARE1024](#) [ARE10A03](#) [ARE10A03Z](#) [ARE10A06](#)
[ARE10A06Z](#) [ARE10A09](#) [ARE10A09Z](#) [ARE10A12Z](#) [ARE10A24](#) [ARE10A24Z](#) [ARE10A4H](#) [ARE10A4HZ](#) [ARE1303](#)
[ARE1306](#) [ARE1309](#) [ARE1324](#) [ARE13A03](#) [ARE13A03Z](#) [ARE13A06](#) [ARE13A06Z](#) [ARE13A09](#) [ARE13A09Z](#)
[ARE13A24](#) [ARE13A24Z](#) [ARE13A4HZ](#) [ARE13A12Z](#) [ARE104H](#) [ARE134H](#) [ARE10A12](#) [ARE1312](#) [ARE13A4H](#)
[ARE1312B01](#) [ARE134HB01](#) [ARE13A12B01](#) [ARE13A12ZB01](#) [ARE13A24B01](#) [ARE13A24ZB01](#) [ARE13A4HB01](#)
[ARE13A4HZB01](#)