

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

## **Features**

- High breakdown Voltage
- Low turn-on voltage
- Guard ring construction for transient protection
- Lead Free Finish/RoHS Compliant("P" Suffix designates RoHS Compliant. See ordering information)

### **Mechanical Data**

- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: S9

# **Maximum Ratings**


Symbol	Rating	Rating	Unit	
V <sub>RRM</sub>	Repetitive Peak Reverse Voltage	100	V	
IF.	Forward DC Current	150	mA	
lo	Average Rectified Output Current at	75	mA	
PD	Power Dissipation	200	mW	
R <sub>JA</sub>	Thermal Resistance Junction to Ambient Air <sup>(1)</sup>	500	°C W	
TJ	Junction Temperature	-55 to +125	°C	
T <sub>STG</sub>	Storage Temperature	-55 to +150	°C	
Electrical Characteristics @ 25°C Unless Otherwise Specified				

Symbol	Parameter		Тур	Max	Units
V <sub>(BR)R</sub>	Reverse Breakdown Voltage (I <sub>R</sub> =100uAdc)	100			V
V <sub>F</sub>	Forward Voltage I⊨=0.1mAdc I⊨=10mAdc I⊧=250mAdc			0.25 0.45 1	V
, I <sub>R</sub>	Leakage Current $(V_R=10Vdc)$ $(V_R=50Vdc)$ $(V_R=75Vdc)$			0.8 2 5	uA
Ст	Total Capacitance (V <sub>R</sub> =0, f=1.0MHz) (V <sub>R</sub> =1.0, f=1.0MHz)		10.0 6.0		pF pF


**BAT46W** 

# 200mW Schottky Diode

100 Volts



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
А	.140	.152	3.55	3.85		
В	.100	.112	2.55	2.85		
С	.055	.071	1.40	1.80		
D		.053		1.35		
Ш	.012	.031	0.30	0.78		
G	.006		0.15			
Η		.01		0.25		
J		.006		0.15		



Notes:

1. Valid provided that electrodes are kept at ambient temperature


www.mccsemi.com

Downloaded from Elcodis.com electronic components distributor

# BAT46W

# **Typical Characteristics**





# www.mccsemi.com

2011/01/01



### **Ordering Information :**

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com