

1. Scope

This Reference specification applies to Chip Ferrite Bead for Automotive Electronics BLM18EG_□H Series based on AEC-Q200.

2. Part Numbering

(ex.)	BL	M	18	EG	601	<u>S</u>	<u>H</u>	1_	<u>D</u>	
	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	
	(1)Pro	oduct ID	(2)T	ype (3)Dimen	sion(L	×W)	(4)Ch	aracteristics	(5)Typical Impedance at 100MHz
	(6)Pe	rformar	ice (7)Categ	ory(for A	utomo	otive E	Electror	nics) (8)Nun	nbers of Circuit
	(9)Pa	ckaging	(D:Tap	oing)						

3. Rating

- · .	rtating									
	Customer MURATA Part Number Part Number		Impedance (Ω) (Under Standard Testing Condition) (*1) (refer to below comment)			Rated Current	(Ω ma	esistance ax.) (*1) to below nment)	Remark	ESD Rank 6:≧25kV
	rait Nullibei	Fait Number	at 100MHz	at 1G	Hz Typical	(mA)	Initial Values	Values After Testing		(AD)
		BLM18EG101TH1D	100±25%	80 min.	140	2000	0.045	0.07	For	
		BLM18EG221TH1D	220±25%	180 min.	300	1000	0.15	0.21	general	6
		BLM18EG331TH1D	330±25%	280 min.	450	500	0.21	0.30	use	
		BLM18EG391TH1D	390±25%	320 min.	520	500	0.30	0.40	(Thin type)	
		BLM18EG121SH1D	120±25%	90 min.	145	2000	0.04	0.06	Г.,	
		BLM18EG181SH1D	180±25%	160 min.	240	2000	0.05	0.08	For	c
		BLM18EG471SH1D	470±25%	340 min.	550	500	0.21	0.30	general use	6
	_	BLM18EG601SH1D	600±25%	450 min.	700	500	0.35	0.45	use	l l

[•] Operating Temperature : -55°C to +125°C • Storage Temperature : -55°C to +125°C

(*1)


Standard Testing Conditions

< Unless otherwise specified > Temperature : Ordinary Temp. (15 °C to 35 °C) Humidity : Ordinary Humidity (25%(RH) to 85%(RH)) < In case of doubt > Temperature : 20°C±2 °C

Temperature : 20°C±2 °C Humidity : 60%(RH) to 70%(RH)


Atmospheric pressure: 86kPa to 106kPa

As for BLM18EG type,Rated Current is derated as right figure depending on the operating temperature.




Operating Temperature (°C)

4. Style and Dimensions



Part Number	Dimension(T)
BLM18EG***TH1	0.5±0.15
BLM18EG***SH1	0.8±0.15

■ Equivalent Circuit



Resistance element becomes dominant at high frequencies.

■ Unit Mass (Typical value)

BLM18EG***TH1: 0.004g BLM18EG***SH1: 0.005g

(in mm)

5. Marking

No marking.

6. Specifications

6-1. Electrical Performance

No.	Item	Specification	Test Method	
6-1-1	Impedance	Meet item 3.	Measuring Frequency: 100MHz±1MHz, 1GHz±1MHz Measuring Equipment: Agilent4291A or the equivalent Test Fixture: Agilent16192A or the equivalent	
6-1-2	DC Resistance	Meet item 3.	Measuring Equipment : Digital multi meter	

6-2. Mechanical Performance(based on Table 13 for FILTER EMI SUPPRESSORS/FILTERS) AEC-Q200 Rev.D issued June. 1 2010


AEC	C-Q200 Rev.D issued June. 1 2010					
		EC-Q200	Murata Specification / Deviation			
No.	Stress	Test Method	·			
3	High Temperature Exposure	1000hours at 125 deg C Set for 24hours at room temperature, then measured.	Meet Table A after testing. Table A Appearance No damage Impedance Change Within ±30% (at 100MHz) DC Meet item 3.			
4	Temperature Cycling	1000cycles -55 deg C to +125 deg C Set for 24hours at room temperature, then measured.	Meet Table B. Table B Appearance No damage Impedance Change (at 100MHz) Within +50/-10%			
5	Destructive Physical Analysis	Per EIA469 No electrical tests	DC Resistance Meet item 3. No defects			
7	Biased Humidity	1000hours at 85 deg C, 85%RH Apply max rated current.	Meet Table A after testing.			
9	External Visual	Visual inspection	No abnormalities			
8	Operational Life	Apply 125 deg C 1000hours Set for 24hours at room temperature, then measured	Meet Table A after testing. If the rated current of parts exceed 1A, the operating temperature should be 85 deg C.			
10	Physical Dimension	Meet ITEM 4 (Style and Dimensions)	No defects			
	Resistance to Solvents	Per MIL-STD-202 Method 215	Not Applicable			
	Mechanical Shock	Per MIL-STD-202 Method 213 Condition F 1500g's (14.7N)/0.5ms/ Half sine	Meet Table A after testing.			
14	Vibration	5g's(0.049N) for 20 minutes, 12cycles each of 3 orientations Test from 10-2000Hz.	Meet Table A after testing.			

1	Resistance	Solder temperature	Pre-heating:150C +/-10 deg,60s to 90s
	to Soldering Heat	260C+/-5 deg C	Meet Table A after testing.
		Immersion time 10s	

		AEC-Q200	Murata Charification / Daviation
No.	Stress	Test Method	Murata Specification / Deviation
17	ESD	Per AEC-Q200-002	Meet Table A after testing. ESD Rank: Meet Item 3.(Rating)
18	Solderability	Per J-STD-002	Method b : Not Applicable 95% of the terminations is to be soldered.
19	Electrical Characterization	Measured : Impedance	No defects
20	Flammability	Per UL-94	Not Applicable
21	Board Flex	Epoxy-PCB(1.6mm) Deflection 2mm(min) 60s minimum holding time	Meet Table A after testing.
22	Terminal Strength	Per AEC-Q200-006	No defects
30	Electrical Transient Conduction	Per ISO-7637-2	Not Applicable

7. Specification of Packaging

7-1. Appearance and Dimensions (8mm-wide paper tape)



Part Number	Dimension (a)
BLM18EG***TH1	0.85 max.
BLM18EG***SH1	1.1 max.
	(in mm)

(1) Taping

Direction of feed

Products shall be packaged in the cavity of the base tape of 8mm-wide,4mm-pitch continuously and sealed by top tape and bottom tape.

(2) Sprocket hole

The sprocket holes are to the right as the tape is pulled toward the user.

(3) Spliced point

The base tape and top tape have no spliced point

(4) Cavity

There shall not be burr in the cavity.

(5) Missing components number

Missing components number within 0.1% of the number per reel or 1 pc., whichever is greater, and are not continuous. The specified quantity per reel is kept.

7-2. Tape Strength


(1)Pull Strength

Top tape

Bottom tape

5N min.

(2)Peeling off force of Top tape



0.1N to 0.6N (Minimum value is typical.)

*Speed of Peeling off:300mm/min

7-3. Taping Condition

(1) Standard quantity per reel

Quantity per 180mm reel: 4000 pcs. / reel

- (2) There shall be leader-tape (top tape and empty tape) and trailer- tape(empty tape) as follows.
- (3) On paper tape, the top tape and the base tape shall not be adhered at the tip of the empty leader tape for more than 5 pitch.
- (4) Marking for reel

The following items shall be marked on a label and the label is stuck on the reel.

(Customer part number, MURATA part number, Inspection number(*1), RoHS marking (*2), Quantity, etc)

*1) « Expression of Inspection No. »

 $\begin{array}{c|c} \square \square & \underline{OOOO} & \underline{\times \times \times} \\ \hline (1) & (2) & (3) \end{array}$

(1) Factory Code

(2) Date First digit : Year / Last digit of year

Second digit : Month / Jan. to Sep. \rightarrow 1 to 9, Oct. to Dec. \rightarrow O, N, D

Third, Fourth digit: Day

(3) Serial No.

*2) « Expression of RoHS marking »

ROHS – <u>Y</u> (<u>△</u>)

(1) (2)

- (1) RoHS regulation conformity parts.
- (2) MURATA classification number


(5) Outside package

These reels shall be packed in the corrugated cardboard package and the following items shall be marked on a label and the label is stuck on the box.


 $(Customer\ name,\ Purchasing\ Order\ Number,\ Customer\ Part\ Number,\ MURATA\ part\ number,$

RoHS marking(*2), Quantity, etc)

(6) Dimensions of reel and taping(leader-tape, trailer-tape)



7-4. Specification of Outer Case



Outer	Case Dime (mm)	nsions	Standard Reel Quantity in Outer Case
W	D	Н	(Reel)
186	186	93	5

^{*} Above Outer Case size is typical. It depends on a quantity of an order.



8-1.Rating

Do not use products beyond the Operating Temperature Range and Rated Current.

8-2.Surge current

Excessive surge current (pulse current or rush current) than specified rated current applied to the product may cause a critical failure, such as an open circuit, burnout caused by excessive temperature rise. Please contact us in advance in case of applying the surge current.

8-3. Fail Safe

Be sure to provide an appropriate fail-safe function on your product to prevent from a second damage that may be caused by the abnormal function or the failure of our products.

8-4. Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

- (1)Aircraft equipment (2)Aerospace equipment (3)Undersea equipment
- (4)Power plant control equipment (5)Medical equipment (6)Disaster prevention / crime prevention equipment
- (7)Traffic signal equipment (8)Transportation equipment (trains, ships, etc.)
- (9) Applications of similar complexity and /or reliability requirements to the applications listed in the above


9. Notice

This product is designed for solder mounting.

Please consult us in advance for applying other mounting method such as conductive adhesive.

9-1. Land pattern designing

• Standard land dimensions (Flow and Reflow soldering)



Soldering	а	b	С
Flow	0.7	2.2 to 2.6	0.7
Reflow	0.7	1.8 to 2.0	0.7
			(in mm)

9-2. Soldering Conditions

Products can be applied to reflow and flow soldering.

(1) Flux, Solder

<i>'</i> '	iux,coiac	
	Flux	Use rosin-based flux, but not highly acidic flux (with chlorine content exceeding 0.2(wt)%.) Do not use water-soluble flux.
	Solder	Use Sn-3.0Ag-0.5Cu solder Standard thickness of solder paste : 100 μm to 200 μm

(2) Soldering conditions


• Pre-heating should be in such a way that the temperature difference between solder and ferrite surface is limited to 150°C max. Also cooling into solvent after soldering should be in such a way that the temperature difference is limited to 100°C max.

Insufficient pre-heating may cause cracks on the ferrite, resulting in the deterioration of product quality.

• Standard soldering profile and the limit soldering profile is as follows.


The excessive limit soldering conditions may cause leaching of the electrode and / or resulting in the deterioration of product quality.

□Flow soldering profile



	Standard Profile	Limit Profile
Pre-heating	150°C, 60s min.	
Heating	250°C, 4s~6s	265°C±3°C, 5s max.
Cycle of flow	2 times	2 times

\square Reflow soldering profile



	Standard Profile	Limit Profile
Pre-heating	150°C~180°C, 90s±30s	
Heating	above 220°C, 30s~60s	above 230°C, 60s max.
Peak temperature	245°C±3°C	260°C, 10s
Cycle of reflow	2 times	2 times


9-3. Reworking with soldering iron

- Pre-heating: 150°C, 1 min
- Tip temperature: 350°C max.
- Soldering time: 3(+1,-0) s
- Soldering iron output: 80W max.
- Tip diameter: φ 3mm max.
- Times: 2times max.

Note: Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the ferrite material due to the thermal shock.

9-4. Solder Volume

Solder shall be used not to be exceeded as shown below.




Accordingly increasing the solder volume, the mechanical stress to product is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance.

9-5. Attention regarding P.C.B. bending


The following shall be considered when designing and laying out P.C.B.'s.

(1) P.C.B. shall be designed so that products are are not subject to the mechanical stress for board warpage. <Products direction>



Products shall be located in the sideways direction (Length:a<b) to the mechanical stress.

(2) Products location on P.C.B. separation.



Products (A,B,C,D) shall be located carefully so that products are not subject to the mechanical stress due to warping the board. Because they may be subjected the mechanical stress in order of A>C>B \cong D.

9-6. Mounting density

Add special attention to radiating heat of products when mounting the inductor near the products with heating. The excessive heat by other products may cause deterioration at joint of this product with substrate.

9-7. Operating Environment

Do not use this product under the following environmental conditions, on deterioration of the Insulation Resistance of the Ferrite material and/or corrosion of Inner Electrode may result from the use.

- (1) in the corrodible atmosphere (acidic gases, alkaline gases, chlorine, sulfur gases, organic gases and etc.)
- (2) in the atmosphere where liquid such as organic solvent, may splash on the products.
- (3) in the atmosphere where the temperature / humidity changes rapidly and it is easy to dew.

9-8. Resin coating

The impedance value may change and/or it may affect on the product's performance due to high cure-stress of resin to be used for coating / molding products. So please pay your careful attention when you select resin. In prior to use, please make the reliability evaluation with the product mounted in your application set.

-9. Cleaning Conditions

Products shall be cleaned on the following conditions.

- (1) Cleaning temperature shall be limited to 60°C max. (40°C max. for IPA)
- (2)Ultrasonic cleaning shall comply with the following conditions, avoiding the resonance phenomenon at the mounted products and P.C.B.

Power:20W/ℓ max. Frequency:28kHz to 40kHz Time:5 min max.

(3)Cleaner

- 1.Cleaner
 - •Isopropyl alcohol (IPA)
- 2.Aqueous agent
 - ●PINE ALPHA ST-100S
- (4) There shall be no residual flux and residual cleaner after cleaning.

In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.

(5)Other cleaning


Please contact us.

9-10. Handling of a substrate

After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.

Bending



Twisting



9-11. Storage Conditions

(1)Storage period

Use the products within 6 months after delivered.

Solderability should be checked if this period is exceeded.

- (2)Storage conditions
 - Products should be stored in

the warehouse on the following conditions.

Temperature : -10°C to 40°C

Humidity : 15% to 85% relative humidity No rapid change on temperature and humidity

- Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.
- Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.
- Products should be stored under the airtight packaged condition.

(3)Delivery

Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

10 . 🕦 Note

- (1)Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- (2) You are requested not to use our product deviating from the agreed specifications.
- (3) The contents of this reference specification are subject to change without advance notice. Please approve our product specifications or transact the approval sheet for product specifications before ordering.