

JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)	
BF20292-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1820 @ 0°C	810	5	38,000 ± 10%	20,000	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC DIMENSIONS ARE IN MILLIMETERS		COMPONENTS COPPODATION							
			THIRD ANGLE PROJECTION	10LERANCE UNLESS OTHERWISE SPECIFIE 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	TITLE	MIN	IATURE COL	D CAT			
A	DIMENSION CHANGES			APPV'D BY DATE	SIZE A	FSCM NO. 55335	DRAWING		2-24B		
REV. NO.	RELEASED DESCRIPTION/ECO NUMBER	2/28/02 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMIT		SCALE		RELEASED DATE 2/28/02	REVISION DATE	12/19/02	NO. A	1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: BF20292-24B