

JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4183-20B	183mm	RGB HIGH OUTPUT	900 @ 0°C	365	5 ± 1	15,000±10%	20,000
BF4220-20B			1,000 @ 0°C	405	5 ± 1	15,000±10%	20,000
BF4418-20B	418mm	KELVIN	1,400 @ 0°C	765	5 ± 1	15,000±10%	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS		JKL COMPONENTS CORPORATION						
			THIRD ANGLE PROJECTION	OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP					
	DELEASED TO OAD	0/47/00	DRAWN BY L. WENGSTROM	APPV'D BY J.K.	DATE 9/17/02	SIZE	FSCM NO. 55335	DRAWING NO.	BF 4	-20B	
REV. NO.		9/17/02 APPV'D DATE	- CAD D MANUAL REVISIO	RAWING	_	SCALE		RELEASED DATE 9/17/		ISION RE	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: BF4220-20B