




Home About Us Products Applications Sales Support Contact Us Search

[Industrial Products](#) > [Industrial Switches](#) > [Square Non-Illuminated Pushbutton Switches](#) > [Square Pushbutton Switches, BXR Series](#)



enlarge

Square Pushbutton Switches, BXR Series

Economical momentary, non-illuminated switches feature "Adjusto-Clip" snap-lock mounting and selection of switching. Bezel trims mounting and enclosed construction protects against dust, dirt, and physical damage. Color pushbuttons have concave face for positive "feel".

Products

Specifications

Need more info? Contact Switchcraft customer service

[Printer friendly version](#)

MOUNTING

Front mount in .620 inch (15.75 mm) minimum square hole. Solder lug/quick-connect terminals accept AMP FASTON® 110 terminals. "Adjusto-Clip" permits mounting in panels from .047 inch (1.19 mm) to .281 inch (7.14 mm) thick.

® FASTON is a registered trademark of AMP INC.

SPECIFICATIONS

Housing: Molded plastic, charcoal gray only.

Pushbutton: Molded plastic; red, black and white standard.

"Adjusto-Clip" Mounting Frame: Copper alloy, plated.

Contact Springs: Copper alloy, plated.

Contacts: Integral, copper alloy, plated. 1-A, 1-C, 2-C

Switching: 250 mA, 30 W max., AC, non-inductive load.

Terminals: Copper alloy, silver-plated.

PART NUMBERS

Pushbutton Color/Part Number			
Red	Black	White	Circuits
Solder Lug/Quick-Connect Terminals			
BXR011	BXR021	BXR051	1-A
BXR013	BXR023	BXR053	1-C
BXR016	BXR026	BXR056	2-C

"ADJUSTO-CLIP" MOUNTING POSITIONS

Position Number	Panel Thickness Inch (mm)	
	Minimum	Maximum
1*	.047 (1.2)	.094 (2.4)
2	.094 (2.4)	.141 (3.6)
3	.141 (3.6)	.188 (4.8)
4	.188 (4.8)	.234 (6.0)
5	.234 (6.0)	.281 (7.1)

* "Adjusto-Clips" normally installed in this position unless otherwise specified.



