

JKL PART NUMBER	LENGTH <b>A</b> +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF5118-20B	118mm	rgb High Output	600	305	5 ± 1	7000 ± 700	20,000
BF5165-20B	165mm		800	800 400		7000 ± 700	20,000
BF5200-20B	200mm WHITE 5400°		850	445	5 ± 1	7000 ± 700	20,000
BF5300-20B	300mm	KELVIN	1000	600	5 ± 1	7000 ± 700	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

				DIMENSIONS ARE IN MILLIMETERS	e	<b>JK</b>	L COMPON	NENTS COR	PORAT	TION
			THIRD ANGLE PROJECTION	OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	TITLE	SIN FLU	GLE LEAD TIF ORESCENT L	PLESS MINIAT .AMP	URE	
_			DRAWN BY	APPV'D BY DATE	SIZE		DRAWING NO. DE	5 20D		
A	6.3 TO 6.2 MAX., ADD 5.0 DIM.	2/29/00	L. WENGSTROM	JK 02/29/00	<b>A</b>	55335	Dr	5-20B		
	RELEASED - CANCEL BF-5mm DIA DRAWING	2/25/00		RAWING -	SCALE		RELEASED	REVISION	REV.	SHEET
RE\ NO.		APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			NONE	DATE 2/25/00	DATE 2/29/00	NO. A	1 <sub>OF</sub> 1

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: BF5118-20B