


JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) TYP.	OPERATING LAMP VOLTAGE VL (Vrms) TYP.	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF2698-20B	98±2.0	5,400°k x = .336 y = .353	690 @ 0°C	275	5 ± 1	30,000 TYP.	35,000 AVG.
BF26188-20B	188±3.0		1115 @ 0°C	405			
BF26214-20B	214±2.0		1150 @ 0°C	460			
BF26285-20B	285±1.5		1525 @ 0°C	610			
BF26318-20B	318±1.5		1710 @ 0°C	685			
BF26360-20B	360±1.5		1940 @ 0°C	775			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH INTENSITY BECOMES 50% OF THE INITIAL RATING.

RATING AT 25°C UNLESS OTHERWISE SPECIFIED.

METRIC  THIRD ANGLE PROJECTION			DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- REF.			JKL COMPONENTS CORPORATION							
D WIRE LENGTH TOLERANCE CHANGE 3/25/08 C BF26285-20B LENGTH TOLERANCE CHANGE 2/3/06 B ADD PART BF2698-20B 2/1/04 A ELECTRICAL CHNG. & ADD BF26318 & BF26360 10/20/04 RELEASED TO CAD MULTI LIST 8/14/03			DRAWN BY L. WENGSTROM APPVD BY L.R. DATE 3/25/08			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		SIZE A FSCM NO. 55335		DRAWING NO. BF 26-20B			
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE		RELEASED DATE 8/14/03		REVISION DATE 3/25/08		REV. NO. D SHEET 1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JKL Components:](#)

[BF26360-20B](#) [BF2698-20B](#)