

JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF5118-20B	118mm	RGB	600	305	5 ± 1	7000 ± 700	20,000
BF5165-20B	165mm	HIGH	800	800 400 5 ± 1		7000 ± 700	20,000
BF5200-20B	200mm	WHITE 5400° KELVIN	850	445	5 ± 1	7000 ± 700	20,000
BF5300-20B	300mm		1000	600	5 ± 1	7000 ± 700	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC	DIMEN IN MIL	ISIONS			KI		OMPON	TIC NIT	S COD	DOD A	TION	
		1	\oplus	OTHERV	ANCE UI VISE SPE _ +/- (NLESS ECIFIED 0.2	TITLE	SIN		EAD TIF				IION
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0		-	FLUORESCENT LAMP							
			DRAWN BY	APPV'D	BY C	DATE	SIZE	FSCM NO.				_		
Α	6.3 TO 6.2 MAX., ADD 5.0 DIM.	2/29/00	L. WENGSTROM	JK	02/29	9/00	Α	55335	NO.	BF	5-20	B		
	RELEASED - CANCEL BF-5mm DIA DRAWING	2/25/00	CADD			SCALE		RELEASE	En	REVISIO	NI .	REV.	SHEET	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			5			2/25/00	DATE	2/29/00	NO. A	1 _{OF} 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: BF5165-20B