







Date	SYM	REVISION RECORD	AUTH	DR.	CK.
3/04/06	B	UPDATED MATERIAL SPEC.	T.B.	B.S.	
4/29/06	C	ADDED CONTACT RESI. INFO.	T.B.	B.S.	
8/06/14	D	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	



Wire Leads shown

## SPECIFICATIONS

Plastic material - Polypropylene, PP-1040  
 Flammability Rating -UL94-HB, UL File NO. E216959  
 Temperature Range: -10°C to +100°C  
 Springs - Nickel Plated Spring Steel  
 Wire - 6" Long, 26 AWG, UL1007, CSA  
 Rivets - Brass, Nickel Plated  
 9Volt Snaps - Brass, Nickel Plated  
 Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000  
 ROHS 2 COMPLIANT

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)		Scale 1=1	Drawn By T.S. Approved By T.B.
Fractional ± .8 (.030)	Title EIGHT "C" CELL HOLDER WITH 6" WIRE LEADS		
Angular ± 3°	Date 8/06/14	Drawing Number BH28CW	