




Date	SYM	REVISION RECORD	AUTH	DR.	CK.
07/05/03	А	ADDED UL FILE #, MTL. INFO. FOR PC PIN	T.B.	B.S.	
07/25/03	В	CHANGED NOTES	T.B.	B.S.	
08/09/03	С	ADDED MOUNTING INSTRUCTION	T.B.	B.S.	
5/27/06	D	REDRAWN. ADDED "ROHS COMPLIANT". UPDATED NOTES	T.B.	B.S.	
11/07/14	Е	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	





PCB LAYOUT



NOTES:

1 MATERIAL

HOUSING: HIGH IMPACT NYLON 66, HALOGEN AND

PHOSPHOR FREE, UL94V-0, UL FILE NO. E48285

RIVETS: BRASS, NICKEL PLATED.

SPRING: 302 STAINLESS STEEL, NICKEL PLATED. CROSSOVER WIRE: 24AWG, UL1007, CSA, TR64 PC PINS: 302 STAINLESS STEEL, NICKEL PLATED.

TEMPERATURE RANGE: -40°C TO +140°C

RESISTANT TO SOLVENTS, COMMON OILS AND REFRIGERANTS

ROHS 2 COMPLIANT

MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT. ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Except as noted)	MPD Mem	ory Protection Devices, Inc					
(and promoted and and any	200 Broad Hollow Road, Farmingdale, New York 11735						
decimal			Scale	Drawn By B.S.			
±.5 (.020)				Approved By T.B.			
Fractional	Title THREE "AAA" CELL HOLDER WITH PC PINS						
± .8 (.030)							
Angular	Date	Drawing Number					
± 3°	11/07/14	ВНЗАААРС					