

Search Results

Evaluate

- FAQ's
- Line Cards
- PDFCable Access ..

Design a Solution


- Part Drawings
- PDFBridle Ring..
- Specification Sheets
- PDFCable Access ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'BR-.75-10-24'

Your search criteria matched only one product, shown below

BR-.75-10-24



- Multiple diameters, thread sizes, and configurations
- Threaded and non -threaded sizes are compatible with spring steel clip (BR -MPCL) clamp providing a solid securing point for the bridle ring
- Other unique labor saving assemblies differentiate from competition – including pre - assemblies with powder actuated fasteners, toggle wings, and clearance holes for user supplied fasteners

| | |
|------------------------------|---|
| Part Number | BR-.75-10-24 |
| RoHS Compliancy Status | Compliant |
| Part Description | Bridle ring, .75" dia., 10- 24 threaded. |
| Material | Low carbon steel with bright zinc electroplate |
| Max. Bundle Capacity (In.) | 0.75 |
| Max. Bundle Capacity (mm) | 19 |
| Overall Height (In.) | 2.0 |
| Overall Height (mm) | 52 |
| Pricing Description | Bridle Ring, .75" Dia., 10- 24 Threaded |
| Ring Size | 3/4" |
| Thread size | 10- 24 threaded |
| Min. Order UOM | PC |
| Min. Order Qty. | 100 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List |  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.