

Accessory Products



Breather Kit (Pressure Compensation Plug)



- · Packaged individually.
- Provides for controlled pressure compensation due to temperature variations (i.e. night/day operation).
- · Recommend two plugs per cabinet in opposite locations.
- Minimum cutout diameter 1.46"

Part No.	Dimensions (Diameter x Depth)	Ship Wt. lbs
SDA412	2.6" x 1.2"	1



Mounting: PG 29 (1.14") thread with union nut, minimum cutout diameter

Material: Polycarbonate UL94VO
Protection: IP45

Color: RAL 7032 beige



Breather Kit (Pressure Compensation Plug)



- · Packaged individually.
- Provides for controlled pressure compensation due to temperature variations (i.e. night/day operation).
- Recommend two plugs per cabinet in opposite locations.
- Pipe Thread 1/2"NPT (actual dia. 0.84")



55")	15.24 (0.6")
31.75 (1.25")	
	27.94 (1.1")

Part No.	BDN4XN1

CSA/A Ex Approvals:	Class I, Zone 1, Ex e II Class I Division 2 Groups ABCD Class II EFG, Class III
Ingress Protection:	IP66, CSA Enclosure Type NEMA 4X
Impact Resistance:	20Nm (7Nm GF Nylon)
Materials:	Durethan BKV 30 N1 30% Glass Filled Nylon O Ring - Nitrile Fixing nut - Brass
Operating Temp:	-50C to +85C

Technical references and DXF downloads available at www.hammfg.com

All dimensions in inches unless specified otherwise

Data Subject to change without notice