

Search Results

- Evaluate
  - FAQ's
  - Product Bulletins
  - PDFObsolete and..
  - Selection Guides
  - PDFConvenience..
- Design a Solution
  - Part Drawings
  - PDFButt Splices..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'BSV10X-E'

Your search criteria matched only one product, shown below

**BSV10X-E**



- Expanded wire entry designed to accommodate wire with a larger insulation thickness
- Designed to splice two solid or stranded wires together to repair or lengthen wires
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal wire stop assures proper length of insertion into terminal barrel
- UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486C

Part Number	BSV10X-E
RoHS Compliancy Status	Compliant
Part Description	Butt Splice, 12– 10 AWG, vinyl insulated.
Product Type	Splices
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.18
Length (mm)	30.0
CE Compliant	No
Insulation	Vinyl
Max. Ins.	0.250
Max. Ins. (mm)	6.4
Panduit Color Code	Yellow
Plating Type	Tinned
Pricing Description	Terminal Convenience Package
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
Wire Range	12 – 10 AWG
Wire Range (mm <sup>2</sup> )	2.5 – 6.0
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.