

## Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output	
<b>8 mm - Embeddable, Miniature Threaded Barrel, Potted-In Cable</b> 	Bi 2-EG08-AG41X	S4562000		2	2-Wire DC	
	Bi 2-EG08-AG41X/S1589	S4562088	weldguard	2		
	Bi 1.5-EG08-AN6X	S4602340			1.5	3-Wire DC NPN
	Bi 1.5U-EG08-AN6X	S4600510	Uprox	1.5		
	Bi 2-EG08-AN6X	S4602140	Ext. Range	2		
	Bi 2-EG08-AN6X/S1589	S4602181	weldguard	2		
	Bi 2U-EG08-AN6X	S4602035	Uprox	2		
	Bi 1.5-EG08-AN7X	S1766110	TTL Compatible	1.5		
	Bi 1.5-EG08-AP6X	S4602240			1.5	3-Wire DC PNP
	Bi 1.5U-EG08-AP6X	S4600500	Uprox	1.5		
	Bi 2-EG08-AP6X	S4602040	Ext. Range	2		
	Bi 2-EG08-AP6X/S100	S4602047	High Temp. 100°C	2		
	Bi 2-EG08-AP6X/S957	S4602008	Flush Mount	2		
	Bi 2-EG08-AP6X/S1589	S4602085	weldguard	2		
	Bi 2-EG08-AP6X/S1610	S4602086-1	armorguard	2		
	Bi 2U-EG08-AP6X	S4602032	Uprox	2		
	Bi 1.5-EG08-Y1	S1003500			1.5	2-Wire DC NAMUR
Bi 2-EG08-AZ14X	S4100001			2	2-Wire AC/DC	
Bi 2-EG08-VP6X	S1604610	Comp. Outputs		2	4-Wire DC PNP	
<b>8 mm - Embeddable, Miniature Threaded Barrel, Potted-In Cable, Teflon Coated</b> 	Bi 2-EGT08-AG41X	S4602540		2	2-Wire DC	
	Bi 1.5-EGT08-AP/S100	S4602256	High Temp. 100°C	1.5	3-Wire DC PNP	

Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	End Cap	Power LED	Output LED	Cable Length/ Cable Mat.	Wiring Diagram #	Wiring Diagrams
10-55 VDC	1000	≤100	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	4	<b>Diagram 1</b> 
	1000	≤100	-25 to +70	IP 67	SS	WG	TROG	N/A	YE	2M/PUR	4	
10-30 VDC	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	1	<b>Diagram 2</b> 
	2000	≤150	-30 to +85	IP 68	SS	PA 12	TROG	N/A	YE	2M/PUR	1	
	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	1	
	3000	≤150	-25 to +70	IP 67	SS	WG	TROG	N/A	YE	2M/PUR	1	
	2000	≤150	-30 to +85	IP 68	SS	PA 12	TROG	N/A	YE	2M/PUR	1	
10-30 VDC	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	2	<b>Diagram 3</b> 
	2000	≤150	-30 to +85	IP 68	SS	PA 12	TROG	N/A	YE	2M/PUR	2	
	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	2	
	3000	≤150	-25 to +100	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	2	
	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	2	
	3000	≤150	-25 to +70	IP 67	SS	WG	TROG	N/A	YE	2M/PUR	2	
	2000	≤150	-30 to +85	IP 68	SS	PA 12	TROG	N/A	YE	2M/PUR	2	
5-30 VDC	5000	Remote	-25 to +70	IP 67	SS	PA 12	TROG	N/A	N/A	2M/PUR	3	<b>Diagram 4</b> 
20-132 VAC 10-140 VDC	20	≤100	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	5	<b>Diagram 5</b> 
10-30 VDC	3000	≤150	-25 to +70	IP 67	SS	PA 12	TROG	N/A	YE	2M/PUR	6	<b>Diagram 6</b> 
10-55 VDC	1000	≤100	-25 to +70	IP 67	TC	PA 12	TC	N/A	YE	2M/PUR	4	
10-30 VDC	2000	≤150	-25 to +100	IP 67	TC	PA 12	TC	N/A	YE	2M/PUR	2	