			-	REV.	DESCRIPTION / ECO NO.			DATE 8/3/99
				_	RELEASED		_	orora
				_				
			-					-
	1							
JKL		STARTING CIRCUIT VOLTAGE	OPERATING		MP VOLTAGE	BRIGHTNESS		ATED
PART NUMBER	COLOR	VS (Vrms)	IL (mAmps)		VL (Vrms)	(CANDELA/m2		OURS
BF26250-24B	LCD HIGH OUTPUT	1300 @ O°C	5		525	30,000	20	,000
	WHITE 11000 ⁰ K RGB					+/- 10%		
	17±2	2:	50±5.0			17±2		-
		2	50±5.0		5 M	17±2	-	*
	5 MAX.	2	+	2	5 M		1	•
	5 MAX.	2	+	.2	5 M		ب ــــــــــــــــــــــــــــــــــــ	+
	5 MAX.	2:	+	.2	5 M		L	+
	5 MAX.	2	+	.2	5 M		LX .	*
	5 MAX.	2	+	.2	5 M		• ux.	4
	5 MAX.	2	+	.2	5 M		L	4
	5 MAX.	2	+	.2	5 M		LX .	4
	5 MAX.	2:	+	.2	5 M		LX.	*
	5 MAX.	2	+	.2	5 M		ux.	*
	5 MAX.	2	+	.2	5 M		LX .	-
3.0	MAX.		+		ZR	AX.		EVISI
3.0 ^{FLE} MINIA	5 MAX.	THODE	↓ 2.6±0		ZR			EVISI
3.0 ^{FLE} MINIA	MAX.	THODE	↓ 2.6±0	UMBE	ZR	AX.		EVISI D BY
3.0 ^{FLE} MINIA	MAX.	THODE	2.6±0 DRAWING N	UMBE DATE	ER BF2	AX.	R	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: BF26250-24B