



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 6720°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) AVERAGE
BF3228-21B	x = .315 y = .295	1190	475	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0			JKL COMPONENTS CORPORATION									
						TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP									
B ELECTRICAL RATING CHANGES A BRIGHTNESS RATING CHANGES RELEASED			8/5/04 8/20/97 12/95			DRAWN BY L. WENGSTROM		APPVD BY DATE J.K. 8/5/04		SIZE A		FSCM NO. 55335		DRAWING NO. BF3228-21B	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE			RELEASED DATE 12/95		REVISION DATE 8/5/04		REV. NO. B		SHEET 1 OF 1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JKL Components:](#)

[BF3228-21B](#)