WWW.PHIHONG.COM



40W Constant Current LED Driver PDA041B Waterproof LED Driver Non-Dimming





Features

- Class 2 per UL1310
- OVP, OCP, Over-Load and Short-Circuit Protection
- >0.9 Power Factor Correction
- 5 Year Warranty

- IP67 Rating waterproof
- THD <20%
- UL 8750 Compliant
- Brownout/Brownout Recovery

Applications

- Down lights
- Area Lights

• Architectural lighting

Safety Approvals

• cUL/UL

Mechanical Characteristics

• Length: 95mm (3.74in)

• Width: 71mm (2.79in)

• Height: 32mm (1.26in)

• Weight: N/A

Output Specifications

Model	DC Output Voltage			Output	Output
	Min.	Typ.	Max.	Current	Power
PDA041B-700B	39V	-	54V	700mA	38W
PDA041B-1A0B	28V	-	40V	1050mA	40W
PDA041B-1A4B	18V	-	26V	1400mA	37W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

PDA041B Characteristics

WWW.PHIHONG.COM

INPUT:

AC Input Voltage Rating

120VAC to 277VAC

AC Input Frequency

47~63Hz

Maximum Input Current

< 0.8A

Leakage Current

0.5mA maximum

Power Factor

 ≥ 0.9

THD

Less than 20%

OUTPUT:

Output Current Ripple

<40%

Efficiency

87% at 277VAC

Environmental:

Temperature

-40 to +82°C Operation case Non-operation -40 to +82°C 20 to 95%

Dimension Diagram unit: mm

Operating Humidity

EMC

FCC 47 Part 18 Class B

Immunity

IEC61000-4-2

IEC61000-4-4

IEC61000-4-5

IEC61000-4-11

Dielectric Withstand (Hi-pot) Test

Primary to secondary: 3000VAC for 1 minute, 10mA

Insulation Resistance

Primary to secondary: >10M Ohm 500VDC, 1 Minute

Features

Short-Circuit Protection

The PSU will withstand a short circuit across the outputs without damage

Input Over Current Protection

The input power line will be fused with a 2A/300V fuse

Output Over-voltage Protection

Auto shutdown

Input / Output Connections

Position	Color	Specification
Input	Black White	AWG16 Solid Wire AWG16 Solid Wire
0.4.4	Red	AWG18 Solid Wire
Output	Black	AWG18 Solid Wire

Warranty

5 Years

32 95 00 70