



ELECTRO-OPTICAL CHARACTERISTICS AT 25°C

PARAMETERS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Active Area	45W		1		mm ²
	95W		5		mm ²
Peak Sensitivity	$V_R = 0V$		880		nm
Responsivity at 880nm		0.5	0.6		A/W
Responsivity at 750nm			0.01		A/W
Responsivity at 650nm			0.005		A/W
Spectral Bandwidth at 50%				60	
Dark Current	45W $V_R = 5V$		0.4	2	nA
	95W $V_R = 5V$		1	5	nA
Shunt Resistance	45W $V_R = 10 mV$		3		Gohm
	95W $V_R = 10 mV$		1		Gohm
Response Time	45W $V_R = 5V, R_L = 50$		1		sec
	95W $V_R = 5V, R_L = 50$		1		sec
Breakdown Voltage	45W $I_R = 10 A$	20	30		V
	95W $I_R = 10 A$	5	10		V
Capacitance	45W $V_R = 0V$		170		pF
	45W $V_R = 5V$		90		pF
	95W $V_R = 0V$		700		pF
	95W $V_R = 5V$		350		pF

ABSOLUTE MAXIMUM RATINGS AT 25°C

Storage and Operating Temperature Range	-55°C to 100°C
Maximum Junction Temperature	100°C
Lead Soldering Temperature (1/16" from case for 10 sec)	240°C

