

RR series, high-precision metal film chip resistors

Thin Film Technology has achieved high performance chip resistors with low price and reliable supply. The parts offer excellent performance and tolerance in TCR, current noise, linearity, for high frequency circuit applications. Precise dimensions minimize errors during mounting. Tight tolerance allow for cost saving due to circuit simplification and elimination of trim pots for adjustment.

SPECIFICATIONS



Dimension (Inch Size)	RR0306 (0201)	RR0510 (0402)	RR0816 (0603)	RR1220 RN73 (0805)	RR1632 (1206)	RR2632 (1210)
L	$0.60\!\pm\!0.05$	$1.00{\pm}0.05$	1.60 ± 0.20	$2.00{\pm}0.20$	$3.20{\pm}0.20$	$3.20{\pm}0.20$
W	$0.30\!\pm\!0.05$	$0.50{\pm}0.05$	$0.80{\pm}0.20$	1.25 ± 0.20	$1.60 {\pm} 0.20$	$2.60{\pm}0.20$
А	$0.12{\pm}0.05$	$0.20{\pm}0.10$	$0.30{\pm}0.20$	$0.40{\pm}0.20$	$0.50 {\pm} 0.20$	$0.50{\pm}0.20$
В	$0.12{\pm}0.05$	$0.25{\pm}0.05$	$0.30{\pm}0.20$	$0.40{\pm}0.20$	$0.45 {\pm} 0.20$	$0.45{\pm}0.20$
Т	$0.23 {\pm} 0.03$	$0.35{\pm}0.05$	$0.40{\pm}0.10$	0.40 ± 0.10	0.40 ± 0.10	$0.40{\pm}0.10$
						(unit : mm)

(RoHS compliant) Completely lead free

Electrical

Туре	RR0306		RR0510		RR0816		RR1220		RN73		RR1632				RR2632					
Power	1/20W		1/16W		1/16W		1/10W		1/10W				1/8W			1/4W				
Tolerance %(code)	±1.0% (F)	±0.5% (D)	±0.5% (D)		±0.5% (D)		±0.5% (D)		±0.1% (B)		±0.5% (D)		±0.1% (B)			±0.5% (D)		±0.1% (B)		
Resistance Range (Ω)	10~ 30	33~ 22k	10~ 97.6	100~ 100k			10~ 97.6		511~ 100k				100~ 200k			10~ 49.9			100~ 330k	
TCR ppm /°C(code)	±100 (R)	±25 (P)	±100 (R)	±25 (P)	±50 (Q)	±25 (P)	±50 (Q)	±25 (P)	±5 (V)	±10 (N)	±50 (Q)	±25 (P)	±5 (V)	±10 (N)	±25 (P)	±50 (Q)	±25 (P)	±5 (V)	±10 (N)	±25 (P)
Resistance Value	E-24 E-24/E-96		/E-96	E-24/E-96 E-24/E-96		E-24/E-96 E-24/E-		/E-96	6 E-24/E-96			E-24/E-96		E-24/E-96						
Operating Temp. Range -55°C~+125°C																				
Max Operating Voltage	15V		25V 7		75	5V 100		0V	10	0V	150V		150V		200V		200V			
Package	-,		10,0 pcs/		5,000 pcs/reel		5,000 pcs/reel		1,000(T1) · 5,000(T5)pcs/reel		1,000(T1) · 5,000(T5)/reel		1,000(T1) · 5,000(T5)pcs/reel			1,000(T1) · 5,000(T5)/reel		1,000(T1) · 5,000(T5)pcs/ree		s/reel

· Contact us also for RL0816-JMP jumper resistor whose dimensions are the same as those of RR0816.

