


MTP PressFit Power Module Three Phase Bridge, 45 A to 100 A



MTP PressFit


**RoHS
COMPLIANT**

FEATURES

- Low V_F
- Low profile package
- Direct mounting to heatsink
- PressFit pins technology
- Low junction to case thermal resistance
- 3500 V_{RMS} insulation voltage
- Designed and qualified for industrial level
- PressFit pins locking technology
PATENT(S): www.vishay.com/patents
- UL approved file E78996 
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

APPLICATIONS

- Power conversion machines
- Welding
- UPS
- SMPS
- Motor drives
- General purpose and heavy duty application

DESCRIPTION

The new MTP module is easy to use thanks to solder less method for contacting PressFit pins to the PCB. The low profile package has been specifically conceived to maximize space saving and optimize the electrical layout of the application specific power supplies.

| PRIMARY CHARACTERISTICS | |
|-------------------------|--------------------|
| I_O | 45 A to 100 A |
| V_{RRM} | 1600 V |
| Package | MTP PressFit |
| Circuit configuration | Three phase bridge |

| MAJOR RATINGS AND CHARACTERISTICS | | | | | |
|-----------------------------------|-----------------|----------------|----------------|-----------------|-------------------|
| SYMBOL | CHARACTERISTICS | VALUES 40MT | VALUES 70MT | VALUES 100MT | UNITS |
| I_O | | 45 | 75 | 100 | A |
| | T_C | 100 | 80 | 80 | °C |
| I_{FSM} | 50 Hz | 270 | 380 | 450 | A |
| | 60 Hz | 280 | 398 | 470 | |
| I^2t | 50 Hz | 365 | 724 | 1013 | A ² s |
| | 60 Hz | 325 | 660 | 920 | |
| $I^2\sqrt{t}$ | | 3650 | 7240 | 10 130 | A ² √s |
| V_{RRM} | | 1600 | | | V |
| T_{Stg} | Range | - 40 to + 150 | | | °C |
| T_J | | - 40 to + 150 | | | |

PATENT(S): www.vishay.com/patents

This Vishay product is protected by one or more United States and international patents.



ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS | | | | |
|-------------------------------------------------|--------------------------------------|-----------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------------|
| TYPE NUMBER | VOLTAGE CODE REVERSE VOLTAGE V | V _{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V | V _{RSM} , MAXIMUM NON-REPETITIVE PEAK V | I _{RRM} MAXIMUM AT T _J = 150 °C mA |
| VS-40MT160P-P, VS-70MT160P-P, VS-100MT160P-P | 160 | 1600 | 1700 | 5 |

| FORWARD CONDUCTION | | | | | | | | |
|------------------------------------------------------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|----------------------------------------------------|----------------|-----------------|-------------------|------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES 40MT | VALUES 70MT | VALUES 100MT | UNITS | |
| Maximum DC output current at case temperature | I _O | 120° rect. to conduction angle | | 45 | 75 | 100 | A | |
| | | | | 100 | 80 | 80 | °C | |
| Maximum peak, one cycle forward, non-repetitive on state surge current | I _{FSM} | t = 10 ms | No voltage reapplied | Initial T _J = T _J maximum | 270 | 380 | 450 | A |
| | | t = 8.3 ms | | | 280 | 398 | 470 | |
| | | t = 10 ms | 100 % V _{RRM} reapplied | | 225 | 320 | 380 | |
| | | t = 8.3 ms | | | 240 | 335 | 400 | |
| Maximum I ² t for fusing | I ² t | t = 10 ms | No voltage reapplied | Initial T _J = T _J maximum | 365 | 724 | 1013 | A ² s |
| | | t = 8.3 ms | | | 325 | 660 | 920 | |
| | | t = 10 ms | 100 % V _{RRM} reapplied | | 253 | 512 | 600 | |
| | | t = 8.3 ms | | | 240 | 467 | 665 | |
| Maximum I ² √t for fusing | I ² √t | t = 0.1 ms to 10 ms, no voltage reapplied | | 3650 | 7240 | 10 130 | A ² √s | |
| Value of threshold voltage | V _{F(TO)} | T _J maximum | | 0.78 | 0.82 | 0.75 | V | |
| Slope resistance | r _t | | | 14.8 | 9.5 | 8.1 | mΩ | |
| Maximum forward voltage drop | V _{FM} | T _J = 25 °C; t _p = 400 μs single junction (40MT, I _{pk} = 40 A) (70MT, I _{pk} = 70 A) (100MT, I _{pk} = 100 A) | | 1.45 | 1.45 | 1.51 | V | |

| INSULATION TABLE | | | | | | | |
|-------------------------|------------------|------------------------------------------------------------------|--|----------------|----------------|-----------------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES 40MT | VALUES 70MT | VALUES 100MT | UNITS |
| RMS insulation voltage | V _{INS} | T _J = 25 °C, all terminal shorted, f = 50 Hz, t = 1 s | | 3500 | | | V |

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | | | | |
|---------------------------------------------------------|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------|----------------|-----------------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES 40MT | VALUES 70MT | VALUES 100MT | UNITS |
| Maximum junction operating temperature range | T _J | | | - 40 to + 150 | | | °C |
| Maximum storage temperature range | T _{Stg} | | | - 40 to + 150 | | | |
| Maximum thermal resistance, junction to case | R _{thJC} | DC operation per module | | 0.27 | 0.23 | 0.19 | K/W |
| | | DC operation per junction | | 1.6 | 1.38 | 1.14 | |
| | | 120° rect. conduction angle per module | | 0.38 | 0.29 | 0.22 | |
| | | 120° rect. conduction angle per junction | | 2.25 | 1.76 | 1.29 | |
| Maximum thermal resistance, case to heatsink per module | R _{thCS} | Mounting surface smooth, flat and greased heatsink compound thermal conductivity = 0.42 W/mK | | 0.1 | | | |
| Mounting torque to heatsink± 10 % | | A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads | | 4 | | | Nm |
| Approximate weight | | | | 65 | | | g |



| CLEARANCE AND CREEPAGE DISTANCES | | | |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|
| PARAMETER | TEST CONDITIONS | MTP PressFit | UNITS |
| Clearance | External shortest distances in air between terminals which are not internally short circuited together | 10.2 | mm |
| Creepage distance | Shortest distance along external surface of the insulating material between terminals which are not internally short circuited together | 13 | |




Fig. 1 - Current Rating Characteristics




Fig. 3 - Maximum Non-Repetitive Surge Current




Fig. 2 - On-State Voltage Drop Characteristics




Fig. 4 - Maximum Non-Repetitive Surge Current




Fig. 5 - Current Rating Nomogram (1 Module Per Heatsink)




Fig. 6 - Current Rating Characteristics




Fig. 8 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 10 - Current Rating Nomogram (1 Module Per Heatsink)




Fig. 11 - Current Rating Characteristics




Fig. 13 - Maximum Non-Repetitive Surge Current




Fig. 12 - On-State Voltage Drop Characteristics




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Current Rating Nomogram (1 Module Per Heatsink)






Fig. 16 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE


- 1** - Vishay Semiconductors product
- 2** - Current rating code

| |
|------------|
| 4 = 45 A |
| 7 = 75 A |
| 10 = 100 A |
- 3** - Circuit configuration code: 0 = Three Phase Bridge
- 4** - Package indicator
- 5** - Voltage code x 10 = V_{RRM} (see Voltage Ratings table)
- 6** - Pinout code (PressFit pins)


CIRCUIT CONFIGURATION

LINKS TO RELATED DOCUMENTS

| | |
|------------|------------------------------------------------------------------------|
| Dimensions | www.vishay.com/doc?95595 |
|------------|------------------------------------------------------------------------|



MTP Three Phase PressFit

DIMENSIONS in millimeters





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.