



Rated cross-section ≤ 1.5 mm²



TOP 1.5GS 7.62/90



modular construction



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	16	10	10
Clamping range max.	mm²/AWG	1.5	14	14

*Overvoltage category III / Pollution severity 3

Additional technical data see page 57

Solder pin length 3.5 mm



Colour

Poles	Type	Cat. No.	Qty.
2	TOP1.5GS2/90	0393360000	100
3	TOP1.5GS3/90	0393460000	100
4	TOP1.5GS4/90	0393560000	50
5	TOP1.5GS5/90	0393660000	25
6	TOP1.5GS6/90	1683990000	20
7	TOP1.5GS7/90	1647310000	20
8	TOP1.5GS8/90	0642460000	20
10	TOP1.5GS10/90	0642560000	20

TOP 1.5GS 7.62/180



modular construction



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	16	10	10
Clamping range max.	mm²/AWG	1.5	14	14

*Overvoltage category III / Pollution severity 3

Additional technical data see page 57

Solder pin length 4.5 mm

Colour

Poles	Type	Cat. No.	Qty.
2	TOP1.5GS2/180	0391360000	100
3	TOP1.5GS3/180	0391460000	50
4	TOP1.5GS4/180	0391560000	50
5	TOP1.5GS5/180	1490460000	25
6	TOP1.5GS6/180	1597060000	20
7	TOP1.5GS7/180	1597070000	20
8	TOP1.5GS8/180	0570960000	20
10	TOP1.5GS10/180	0571160000	20

Accessories	Page
Marking	42
Fixing	-
Miscellaneous	45

Accessories	Page
Marking	42
Fixing	-
Miscellaneous	45