


- FEATURES**  
 G4 Base - Non-Polarized  
 Wide Input Voltage Range  
 Low Power Usage  
 Omni Directional Light Distribution  
 Efficacy of 47Lm/Watt

VOLTAGE AC/DC			WATTS			ILLUMINANCE FLUX lm TYP	COLOR DEGREE K
MIN	NOM	MAX	MIN	NOM	MAX		
8	12	30	1.2	1.4	1.6	75	3500

<b>METRIC</b>		DIMENSIONS ARE IN MILLIMETERS		<b>JKL COMPONENTS CORPORATION</b>			
 THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/-					
DRAWN BY		APPV'D BY		DATE	SIZE	FSCM NO.	DRAWING NO.
L. WENGSTROM		L.R.		5/9/12	<b>A</b>	<b>55335</b>	<b>Z-G4-15WW</b>
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE	RELEASED DATE	REVISION DATE	REV. NO.
				NONE	5/9/12		1 OF 1

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
	RELEASED & CANCEL PL-0912-01	5/9/12