



### Main

Range of product	Harmony XVD Optimum
Product or component type	Complete miniature beacon
Beacon/Indicator bk unit type	Base unit direct fixing Illuminated unit
Signalling type	Steady
Mounting diameter	45 mm
Component name	XVDLS
Material	Glass reinforced polyamide base unit Polycarbonate illuminated unit
Light source	Bulb not included red
Bulb type	Incandescent BA 15d
[Us] rated supply voltage	<= 230 V
Power dissipation in W	< 5 W

### Complementary

Connections - terminals	Screw clamp terminals <= 1 x 1.5 mm <sup>2</sup> with cable end
Cable entry	1 tapped entry Pg 7
[Ui] rated insulation voltage	250 V IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV IEC 60947-1
Product weight	0,08 kg

### Environment

Product certifications	CSA UL
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Class of protection against electric shock	Class II IEC 60536
IP degree of protection	IP40 IEC 60529
RoHS EUR conformity date	0907
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.