

## Fuse plug - ST 1-SILED 12 - 0920423

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 10 A, Length: 45.4 mm, Width: 9.9 mm, Color: black

The figure shows a similar product



### Key commercial data

Packing unit	50 pc
GTIN	 4 017918 010232
Weight per Piece (excluding packing)	9.84 g
Custom tariff number	85369010
Country of origin	Poland
Note	Made to Order (non-returnable)

### Technical data

#### General

Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

#### Dimensions

Width	9.9 mm
Length	45.4 mm

#### General

Fuse	G / 6,3 x 32
Insulating material group	CTI 600
Nominal current $I_N$	10 A
Nominal voltage $U_N$	400 V (In the event of a defective fuse, the downstream circuit is not disconnected.)

# Fuse plug - ST 1-SILED 12 - 0920423

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149

### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC002018
ETIM 5.0	EC002018

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

## Accessories

Accessories

Documentation

## Fuse plug - ST 1-SILED 12 - 0920423

### Accessories

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block



---

Phoenix Contact 2015 © - all rights reserved  
<http://www.phoenixcontact.com>