

Fuse plug - ST 1-SILED 24 - 0920384

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 10 A, Length: 45.4 mm, Width: 9.9 mm, Color: black

The figure shows a similar product

Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 010218 |
| Weight per Piece (excluding packing) | 9.84 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Poland |

Technical data

General

| | |
|---|-------|
| Color | black |
| Insulating material | PA |
| Inflammability class according to UL 94 | V2 |

Dimensions

| | |
|--------|---------|
| Width | 9.9 mm |
| Length | 45.4 mm |

General

| | |
|-------------------------------------|---|
| Fuse | G / 6,3 x 32 |
| Insulating material group | CTI 600 |
| Nominal current I_N (lower level) | 10 A |
| Nominal voltage U_N | 400 V (In the event of a defective fuse, the downstream circuit is not disconnected.) |

Fuse plug - ST 1-SILED 24 - 0920384

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141145 |
| eCl@ss 5.1 | 27141145 |
| eCl@ss 6.0 | 27141149 |
| eCl@ss 7.0 | 27141149 |
| eCl@ss 8.0 | 27141149 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC002018 |
| ETIM 5.0 | EC002018 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals

Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details

Fuse plug - ST 1-SILED 24 - 0920384

Approvals

GOST 

GOST 