

This document was generated on 11/12/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:0714390364Status:Active | | |
|--|---|---|
| | itch Mezzanine IEEE 1386 Receptacle, Surface Mount, Dual Row, Tube, 0.76μm (30μ") Gold (Au), 64 Circuits Pick and Place Cap | |
| Documents: <u>3D Model</u> <u>Drawing (PDF)</u> | Product Specification PS-71436-9999 (PDF) RoHS Certificate of Compliance (PDF) | Series |
| Agency Certification | | image - Reference only |
| CSA | LR19980 | |
| UL | E29179 | EU RoHS China RoHS |
| General Product Family Series Application Comments | PCB Receptacles <u>71439</u> Board-to-Board, Signal Plugs | ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status Low-Halogen |
| Overview | PMC | |
| Product Name | Mezzanine | Need more information on product environmental compliance? |
| Physical Circuits (Loaded) Color - Resin Flammability Glow-Wire Compliant Lock to Mating Part Mated Height Material - Metal Material - Plating Mating Material - Plating Termination Material - Resin Number of Rows Orientation PCB Locator PCB Retention PCB Thickness - Recommended Packaging Type Pitch - Mating Interface Plating min - Termination Polarized to PCB Robotic Placement Surface Mount Compatible (SMC) Temperature Range - Operating | 64 Natural 94V-0 No Yes 10.00mm (.394"), 8.00mm (.315"), 9.00mm (.354") Phosphor Bronze Gold Tin High Temperature Thermoplastic 2 Vertical Yes None 1.60mm (.063") Tube 1.00mm (.039") 0.762μm (30μ") 1.905μm (75μ") No Pick and Place Cap N/A -55°C to +85°C | Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate of Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions. Search Parts in this Series <u>71439</u> Series <u>Mates With</u> <u>714360</u> for Stack Height 8.00mm (.315"), <u>714361</u> for Stack Height 9.00mm (.354"), <u>714362</u> for Stack Height 10.00mm (.394") |
| Termination Interface: Style Electrical Current - Maximum per Contact | Surface Mount | |
| Voltage - Maximum | 100V | |
| Solder Process Data Lead-free Process Capability Process Temperature may C | Reflow Capable (SMT only) | |

260

Lead-free Process Capability Process Temperature max. C

Material Info

Country of Origin

US

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-70873-014, PK-70873-063 PS-71436-9999, RPS-71436-002, RPS-71436-003 SDA-71439-0***

This document was generated on 11/12/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION