


SPRING-LOADED PINS

DISCRETE SPRING-LOADED CONTACTS • SURFACE MOUNT

0900-0

0900-0-15-20-76-14-11-0


"Legacy P/N 0900-0-00-00-00-00-11-0"
Short stroke, Surface mount



0900-1 ⇨ 4,8

0900-X-15-20-75-14-11-0

"Legacy P/N 0900-X-00-00-00-00-11-0"
Standard stroke, Surface mount




Basic Part Number	Length A
0900-1	.177
0900-2	.197
0900-3	.217
0900-4	.236
* 0900-8	.155

* 0900-8 has a .0195 Mid Stroke & .039 Max. Stroke
Order as:
0900-8-15-20-76-14-11-0

0934

0934-0-15-20-74-14-26-0


Standard stroke, Surface mount



0936

0936-0-15-20-75-14-11-0


Standard stroke, Surface mount



0907-0 ⇨ 9

0907-X-15-20-75-14-11-0

Standard stroke, Surface mount, Mid profile
Also available with insulated sleeve, see page 19.4




Basic Part Number	Length A
0907-0	.255
0907-1	.275
0907-2	.295
0907-3	.315
0907-4	.335
0907-5	.350
0907-6	.370
0907-7	.390
0907-8	.410
0907-9	.430

0928

0928-0-15-20-77-14-11-0


Long stroke, Surface mount



0913

0913-0-15-20-77-14-11-0


Long stroke, Surface mount, Mid profile



0925

0925-0-15-20-73-14-26-0


Standard stroke, Surface mount
Reduced plunger



0927

0927-0-15-20-75-14-11-0


Standard stroke, Surface mount, Mid profile



0905

0905-0-15-20-75-14-11-0

"Legacy P/N 0905-0-00-00-00-00-11-0"
Standard stroke, Surface mount, High profile



Material Specifications:

Sleeve & Plunger Material: Copper Alloy
Spring Material: Beryllium Copper
Sleeve & Plunger Finish: 20 μ" Gold over Nickel
Spring Finish: 10 μ" Gold over Nickel
Dimensions: Inches
Tolerances On: Lengths: ± .006
 Diameters: ± .002
 Angles: ± 2°



Mechanical & Electrical Specifications:

Durability: 1,000,000 cycles
Current Rating: 2A continuous, 3A peak
Contact Resistance: 20 mΩ max.
Environmental Specifications:
Operating temperature range: -55/+125°C
73, 74, 75, 76, 77 Springs are not interchangeable

Order Code: 09XX - X - 15 - 20 - 7X - 14 - XX - 0

Spring Number

Spring Number	Mid. Stroke	Max. Stroke	Force @ Mid. Stroke	Initial Force (Pre-Load)
73	.0275	.055	60 g	25 g
74	.0275	.055	50 g	15 g
75	.0275	.055	60 g	25 g
76	.0195	.039	60 g	25 g
77	.045	.090	60 g	25 g



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mill-Max:

[0900-7-00-00-00-00-11-0](#) [0905-0-00-00-00-00-11-0](#) [0900-6-00-00-00-00-11-0](#) [0900-5-00-00-00-00-11-0](#) [0907-9-15-20-75-14-11-0](#) [0907-5-15-20-75-14-11-0](#) [0907-1-15-20-75-14-11-0](#) [0907-7-15-20-75-14-11-0](#) [0907-3-15-20-75-14-11-0](#) [0907-2-15-20-75-14-11-0](#) [0907-6-15-20-75-14-11-0](#) [0907-4-15-20-75-14-11-0](#) [0907-8-15-20-75-14-11-0](#) [0907-0-15-20-75-14-11-0](#) [0905-0-15-20-75-14-11-0](#) [0925-0-15-20-73-14-26-0](#) [0927-0-15-20-75-14-11-0](#) [0928-0-15-20-77-14-11-0](#) [0934-0-15-20-74-14-26-0](#) [0936-0-15-20-75-14-11-0](#) [0913-0-15-20-77-14-11-0](#) [0900-8-15-20-76-14-11-0](#) [0900-0-15-20-76-14-11-0](#) [0900-1-15-20-75-14-11-0](#) [0900-2-15-20-75-14-11-0](#) [0900-3-15-20-75-14-11-0](#) [0900-4-15-20-75-14-11-0](#) [0907-8-15-00-00-00-11-0](#) [0907-6-15-00-00-00-11-0](#) [0907-0-15-00-00-00-11-0](#) [0907-4-15-00-00-00-11-0](#) [0907-7-15-00-00-00-11-0](#) [0907-5-15-00-00-00-11-0](#) [0907-2-15-00-00-00-11-0](#) [0907-1-15-00-00-00-11-0](#) [0907-9-15-00-00-00-11-0](#) [0907-3-15-00-00-00-11-0](#) [0900-6-15-20-75-14-11-0](#) [0905-0-15-00-00-00-11-0](#) [0900-5-15-20-75-14-11-0](#) [0900-7-15-20-75-14-11-0](#)