

Axial Lead and Cartridge Fuses

Midget

500 Volt Slo-Blo® Type Fuse FLQ Series




ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
135%	1/10-30	1 hour, Maximum
200%	32/10-30	12 seconds, Minimum
	0-3	5 seconds, Minimum

AGENCY APPROVALS: Listed by Underwriters Laboratories and Certified by CSA.

INTERRUPTING RATING: 10,000 amperes at 500 VAC.

PATENTED



ORDERING INFORMATION:

Cartridge Catalog Number	Ampere Rating	AC Voltage Rating	Nominal Resistance Cold Ohms
FLQ 1/10	.100	500	188.0
FLQ 1/8	.125	500	125.9
FLQ 15/100	.150	500	87.0
FLQ 3/16	.187	500	45.5
FLQ 2/10	.200	500	35.109
FLQ 1/4	.250	500	9.7
FLQ 3/10	.300	500	7.4
FLQ 4/10	.400	500	4.325
FLQ 1/2	.500	500	2.76
FLQ 6/10	.600	500	1.88
FLQ 8/10	.800	500	1.03
FLQ 1	1	500	.7864
FLQ 1 1/8	1.125	500	.652
FLQ 1 1/4	1.25	500	.509
FLQ 1 1/2	1.5	500	.3835
FLQ 1 9/10	1.6	500	.296
FLQ 2	2	500	.2086
FLQ 2 1/4	2.25	500	.1563
FLQ 2 1/2	2.5	500	.1381
FLQ 3	3	500	.0954
FLQ 3 2/10	3.2	500	.0938
FLQ 3 1/2	3.5	500	.0732
FLQ 4	4	500	.0618
FLQ 4 1/2	4.5	500	.0463
FLQ 5	5	500	.0348
FLQ 5 9/10	5.6	500	.0327
FLQ 6	6	500	.0284
FLQ 6 1/4	6.25	500	.0263
FLQ 7	7	500	.0212
FLQ 8	8	500	.01830
FLQ 9	9	500	.01540
FLQ 10	10	500	.01563
FLQ 12	12	500	.01176
FLQ 14	14	500	.00740
FLQ 15	15	500	.00690
FLQ 20	20	500	.004063
FLQ 25	25	500	.002920
FLQ 30	30	500	.002816

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

[0FLQ02.5T](#) [0FLQ003.T](#) [0FLQ025.T](#) [0FLQ.187T](#) [0FLQ.300T](#) [0FLQ005.T](#) [0FLQ6.25T](#) [0FLQ03.5T](#) [0FLQ007.T](#)
[0FLQ002.T](#) [0FLQ006.T](#) [0FLQ.400T](#) [0FLQ.600T](#) [0FLQ.100T](#) [0FLQ.150T](#) [0FLQ012.T](#) [0FLQ001.T](#) [0FLQ01.5T](#)
[0FLQ015.T](#) [FLQ.600](#) [0FLQ.200T](#) [0FLQ020.T](#) [0FLQ008.T](#) [FLQ.250](#) [0FLQ01.6T](#) [0FLQ009.T](#) [0FLQ1.25T](#)
[0FLQ05.6T](#) [0FLQ04.5T](#) [0FLQ2.25T](#) [0FLQ.125T](#) [0FLQ010.T](#) [0FLQ030.T](#) [0FLQ1.12T](#) [0FLQ.250T](#) [0FLQ03.2T](#)
[0FLQ014.T](#) [0FLQ004.T](#) [0FLQ.500T](#) [0FLQ.800T](#)