

Important notes about Classic Panel Mount Indicator Catalog Pages

SCROLL DOWN TO VIEW CATALOG PAGE

This catalog page is out-of-print and is used with the understanding that the information shown could be out-of-date. In many cases, part numbers shown on this page are discontinued. Most notably, many "Complete Assembly" parts, which consist of a cap and a base, can no longer be ordered by the 14-digit ordering code. To obtain these parts, please order the cap and base part numbers separately. This process provides the components contained with the original "Complete Assembly" part number.

All Dialight Classic Panel Mount Indicators need a leading 3-digit numerical series. In some cases, this catalog will show a 2-digit series. In this case, please add a leading zero. For example, 81-0211-300 becomes **0**81-0211-300.

Part numbers listed on Dialight catalog pages designate parts with Red lenses. For ordering lens colors other than red, consult the chart below. In most cases, the color is dictated by the 7th digit. For example, 095-093<u>2</u>-003 for a green cap.

Lens Colors	
1 - Red	5 - White
2 - Green	6 - Light Yellow
3 - Yellow	7 - Clear
4 - Blue	

Click here for a cross reference guide to assembly part numbers.

Click here to view Frequently Asked Questions concerning Panel Mount Indicators.

SCROLL DOWN TO VIEW CATALOG PAGE

Non-Dimming Incandescent Indicators



Finish

-black nickel

3-polished chrome

1-white nickel

T-1 3/4 MIDGET

FLANGE BASE

Resistor

0--none

Example: 8-1830-0111-101 (white nickel finish,

no resistor, brass hardware)

How to designate the Three Digit Part Number Suffix (-XXX)

*For 2 terminal requirements, assembly is supplied with 2 insulating washers and a lug. Mounting hole becomes 9/16".

Hardware

3-water-tight on the face of the panel 7-insulated mtg.*

1-brass


See lamp ratings on page J. ONE TERMINAL - FULLY INSULATED for use on grounded circuits.

FOR FRONT MOUNTING IN 15/32" CLEARANCE HOLE

MEET OR EXCEED ENVIRONMENTAL AND OPERATIONAL REQUIREMENTS OF MIL-L-7806 AND MIL-L-3661

MATERIALS AND FINISHES

- Mounting Bushing: Standard— Brass, black nickel finish.
 Optional— Polished chrome or white nickel finish.
- Mounting Nut: Brass, white nickel finish.
- Internal-tooth Lockwasher: Phosphor bronze, white nickel finish.
- Terminals: Soldering
 — Brass, hot tin dip.
 Screw
 — Brass, cadmium plated with yellow iridescent chromate finish.
- Insulation: Per MIL-L-7806.



Part numbers listed in this catalog designate products with RED lens. For ordering lens colors other than red, consult chart on page 4C.

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

<u>008-0112-203</u> <u>008-1930-01-203</u> <u>008-0133-200</u> <u>008-0137-203</u> <u>008-0134-200</u> <u>008-0137-200</u> <u>008-0132-200</u> <u>00</u>