

## Smart IP Access - Extend KVM control over IP

MODEL NUMBER: **0SU51068**



### Description

#### Add remote IP access to existing servers

Smart IP Access is an IP device that provides remote KVM access to servers and network devices. It provides access via LAN, WAN, or Internet connection to either a single server or to mixed server environments. Smart IP Access is ideal for data centers, high-density server environments, and medium to large businesses that are managed by legacy KVM switches.

#### Preserve your investment

Smart IP Access can be attached to almost any switch or server, making it the perfect add-on device and preserving your existing investment. It comes with configuration definitions for all Tripp Lite and most 3rd party KVM switches.

#### Built-in Serial control

Smart IP Access provides built in remote control to two serial devices. For example, Serial control of power management enables you to reboot remotely and to power servers on and off from any location.

#### 128-bit SSL security

Smart IP Access offers industry standard, 128-bit SSL encryption to prevent security breaches. In addition, the dual IP connection provides redundancy and security.

### Features

- Adds remote KVM control servers, computers, and KVM switches
- Features two ports for remote control of serial devices

### Highlights

- Adds remote KVM control servers, computers, and KVM switches
- Features two ports for remote control of serial devices
- Features dual NIC ports for network redundancy and security
- Able to utilize a standard 56Kbps analog modem connection, while allowing adaptive and configurable bandwidth consumption when accessed via LAN
- SNMP traps for monitoring Smart IP Access events and operation
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### System Requirements

#### Operating System

- Host Computer - DOS, Windows, Novell, Linux
- Client Computer - Windows with IE 6.0 or higher

#### Resolution

- Host Computer: Up to 1600 x 1200 @ 85Hz
- Client Computer: Recommended - client computer resolution should be higher than resolution on the host computer

#### Package Includes

- Smart Access Unit
- KVM Cable Kit
- RS232 Cable
- Rackmount Kit



- Features dual NIC ports for network redundancy and security
- Able to utilize a standard 56Kbps analog modem connection, while allowing adaptive and configurable bandwidth consumption when accessed via LAN
- SNMP traps for monitoring Smart IP Access events and operation
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

OVERVIEW	
Users	1
PHYSICAL	
Color	Black
ENVIRONMENTAL	
Storage Temperature Range	-40 to 70 C / -40 to 158 F
Relative Humidity	80% Non-Condensing
Operating Temperature	0 to 40 C / 32 to 104 F
CONNECTIONS	
PC/Server Connections	VGA; PS/2
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>