

All categories

Search term



Your shopping cart

Products

MyHARTING

Downloads / Catalogue order

Repairservice

Han 16B-HMC-g-R

[Spotted an error?](#) | [Print page](#) | [Back](#)

Image is for illustration purposes only.
Please refer to product description.

[Features](#)[Material properties](#)[Dimensions and weight](#)[Version](#)[Norms and specifications](#)

Part number:	09 30 216 0803
Description:	Han 16B-HMC-g-R
Type sheet:	PDF

[Login to MyHARTING](#)
for pricing and stock checkQuantity: [Shopping cart](#)[Email inquiry](#)

Need assistance?

**Customer service****Your HARTING customer
service representative:****866-278-0306**[CustomerService-USA@HA ...](mailto:CustomerService-USA@HA...)

Catalogue

Industrial Connectors Han® -
Page 532[Browse](#)[Download](#)

Features

Mating cycles:	>= 10,000
RoHS conformity:	Yes
Size:	16 B
Material, locking lever:	polycarbonate + stainless steel
Lever type:	single locking lever
Type of hood/housing:	Hoods
Series:	Han® B HMC
Limiting temperature, min.:	-40 °C
Limiting temperature, max.:	125 °C

[Top](#)

Material properties

Colour, locking element:	RAL 7037 (grey)
Surface, hood/housing:	powder-coated
Material, seal:	NBR
Colour, hood/housing:	RAL 7037 (grey)
Material, hood/housing:	aluminium die-cast

[Top](#)

Dimensions and weight

Net Weight:	231.4 g
--------------------	---------

[Top](#)

Version

Hoods and Housings: Case of operation:	Metal hoods/housings for industrial applications
Size:	-
Cable entry:	without cable entry
Style:	High construction

[Top](#)

Norms and specifications











Flammability locking lever acc. to UL 94:	V 0
Protection class acc. to UL 50:	NEMA type 4/4X/12
Approval GL:	Yes
Degree of protection acc. to DIN EN 60 529:	IP65

[Top](#)

Downloads

Title	Download
Type sheet	PDF
Type sheet	DXF
Type sheet	CGM
CAD data 3D	STEP
CAD data 3D	JT
Industrial Connectors Han® - Page 532	PDF

Recently viewed - [Delete](#)

 <p>Han 16B-HMC-g-R</p> <p>Show product details</p>	 <p>Han 10B-HMC-asg2-LB-M25</p> <p>Show product details</p>
 <p>Han E HMC male contact Au AWG 19</p> <p>Show product details</p>	 <p>Han 24B-HMC-asg2-LB-M25</p> <p>Show product details</p>
 <p>Han D M crimp contact 2,5 mm² Au/HMC</p> <p>Show product details</p>	 <p>Han 16B-HMC-asg2-LB-M25</p> <p>Show product details</p>
 <p>Han E HMC female contact Au AWG 26-22</p> <p>Show product details</p>	 <p>Han D M crimp contact 0,75 mm² Au/HMC</p> <p>Show product details</p>
 <p>Han 16B-HMC-gs-R-M32</p> <p>Show product details</p>	 <p>Han E HMC female contact Au AWG 12</p> <p>Show product details</p>

Recently searched - [Delete](#)

- All categories: [09302100803](#) (1)
- All categories: [19302160252](#) (1)
- All categories: [19302240292](#) (1)
- All categories: [11000009601](#) (1)
- All categories: [19410060301](#) (1)
- All categories: [han_eco](#) (188)
- All categories: [19410012700](#) (1)
- All categories: [yellock](#) (164)



