

Connector - PRC 5-FC-FS6 8-21 - 1410656


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PRC connector, black, 5-pos., 1.5 mm² ... 6 mm²/630 V/30 A, with screw connection, for cables with a diameter of 8 mm ... 21 mm.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 904247
Weight per Piece (excluding packing)	103.2 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General data

Number of positions	5
Protection class	II
Color	black
Locking type	Snap-in locking
Insertion/withdrawal cycles	50
Pull-out-force	150 N ± 50 N
Insertion force	40 N ± 10 N

Connection data

Rated current	30 A (with 6 mm ² conductor cross section)
Rated voltage (III/2)	690 V
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	6 mm ²
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	6 mm ²
Torque	1 Nm
Type of contact	Screw contacts

Connector - PRC 5-FC-FS6 8-21 - 1410656

Technical data

Material data

Contact material	Cu
Contact surface material	silver-plated
Contact carrier material	mPPE
Material of grip body	mPPE
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27279220
eCl@ss 8.0	27440102

ETIM

ETIM 4.0	EC002641
ETIM 5.0	EC002635

Approvals

Approvals


Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 	
mm ² /AWG/kcmil	14-10
Nominal current I _N	30 A
Nominal voltage U _N	600 V

Connector - PRC 5-FC-FS6 8-21 - 1410656


Approvals

cUL Listed	
mm ² /AWG/kcmil	14-10
Nominal current I _N	30 A
Nominal voltage U _N	600 V


cULus Listed	
--------------	--

Drawings

Dimensional drawing



Schematic diagram



Connector pin assignment