



RELAYS, CONTACTORS & SWITCHES

SLIDE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

TSS11DG1PC04=SLIDE SWITCH SPDT

Alcoswitch | TSS

1571982-2

TE Internal Number: 1571982-2

Alias ID: TSS11DG1PC04

Always EU RoHS/ELV Compliant

Configuration (Pole-Throw) **Single Pole - Double Throw**

Mounting Angle **Vertical**

Contact Base Material **Copper**

Number of Actuators **Single**

Number of Positions **2**



Product Drawings

SLIDE SWITCH TSS11 AND TSS21 SERIES

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

| | | |
|-----------------------|------------------------|-------------------|
| Product Type Features | Actuator Style | Flush, Top |
| | Threaded Case | Without |
| | Terminal Configuration | Standard |
| | Product Type | Switch |
| | Switch Type | Slide |

| | | |
|------------------------|----------------------------|-----------------------------------|
| Configuration Features | Configuration (Pole-Throw) | Single Pole - Double Throw |
| | Number of Actuators | Single |
| | Number of Positions | 2 |
| | Operating Function | On None On |
| | Terminals Connected | 1-2 |

| | | |
|---------------|-------------------|------------------|
| Body Features | Actuator Material | Polyester |
| | Actuator Color | Black |

| | | |
|------------------|-----------------------|---------------|
| Contact Features | Contact Base Material | Copper |
| | Contact Plating | Gold |

| | | |
|----------------------|------------------|-----------|
| Termination Features | Termination Type | PC |
|----------------------|------------------|-----------|

| | | |
|-----------------------|--------------------------|---------------------|
| Mechanical Attachment | Mounting Angle | Vertical |
| | Mounting Type | Through Hole |
| | PCB Mount Retention Type | Extended |

| | | |
|------------|-----------------|----------------------------|
| Dimensions | PCB Tail Length | 3.3 mm [.13 in] |
| | Length | 10.2 mm [.402 in] |
| | Actuator Length | 2.8 mm [.1102 in] |
| | Width | 5.23 mm [.206 in] |

| | | |
|------------------------|-----------------|-------------|
| Identification Marking | Stamped Marking | With |
|------------------------|-----------------|-------------|

| | | |
|--------------------|------------------------|-----------------|
| Industry Standards | UL Flammability Rating | UL 94V-0 |
|--------------------|------------------------|-----------------|

[VIEW ALL PRODUCT COMPLIANCE](#)

