

- A. Black ABS plastic cap.
- B. 300 series stainless steel backplate (0.015" thick).
- C. Two 4mm snap studs machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force. Compatible with Desco Dual-Wire Coil Cords ONLY (not including MagSnap[®] or MagSnap360[™] products).
- D. Premium metal expansion wrist strap. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.630".

- E. .002" polyphenylsulfone sheet is laminated to each link before assembly. Provides >5,000 volt RMS insulation per ASTM D149. Will not flake or peel.
- F. Black ABS plastic insulator separates band into halves.
- G. Underwriters' Laboratory listed 90P1C.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

		CIRCUMEFERENCE		
ITEM	BAND SIZE	MIN	MAX	WIDTH
<u>19844</u>	Small	5.5" (140mm)	9" (229mm)	0.630"
<u>19842</u>	Medium	6" (152mm)	11" (279mm)	0.630"
<u>19840</u>	Large	7" (178mm)	12" (305mm)	0.630"

Specifications and procedures subject to change without notice. Unless otherwise noted, tolerance ±10%

*U.S. Patents 6.052.053 and 6.205.408



See Drawing 09163 for details on Jewel[®] Coil Cords

Jewel[®] Premium Metal Expansion Dual-Wire Wrist Strap, 4mm

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407	DRAWING NUMBER 09165	november
DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172	09165	2016

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Desco: <u>19844</u> <u>19842</u> <u>19840</u>