| | |

1825097-7 Product Details



1825097-7

TE Part Number: 1825097-7

Add to Part List

Pushbutton Switches

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Switch Mechanical
- Not Tactile
- Single Pole Single Throw Configuration (Pole-Throw)
- Contact Rating = 0.4VA
- Process Sealed

View all Features | Find Similar **Products**

Live Product Chat

Quick Links

- Check Pricing & <u>Availability</u>
- Search for Tooling
- <u>Product Feature</u> <u>Selector</u>
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• PUSHBUTTON SWITCH, TPB SERIES (PDF, English)

Catalog Pages/Data Sheets:

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

• None Available

Additional Information:

Product Line Information

Related Products:

Toolina

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch Mechanical
- Tactile = No
- Configuration (Pole-Throw) = Single Pole -Single Throw
- Mount Angle = Right Angle
- Termination Type = Printed Circuit
- Actuator Style = Round
- Comment = Each switch is provided with a disposable boot used only during cleaning operation.; No center terminal

Electrical Characteristics:

• Contact Rating = 0.4VA

Body Related Features:

- <u>Series</u> = TP-ES
- Mount Style = Through-Hole
- Actuator Length (mm [in]) = 3.48 [0.137]
- Actuator Profile = Extended
- Actuator Color = Red
- Bushing Diameter = 4.78 [.188]
- Case Material = Polyester
- Actuator Material = Polyamide

Contact Related Features:

• Contact Plating = Gold over Nickel

Housing Related Features:

- Process Sealed = Yes
- Low Profile = No
- Bushing Style = Unthreaded

Configuration Related Features:

- Operating Function = Normally Open, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 50.00 400.00 [1.770 - 14.120]
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

Temperature Rating = High

Packaging Related Features:

Packaging Method = Loose Piece

Other:

• Brand = Alcoswitch