

Honeywell Sensing and Control

Search




11TL1-61 ( Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TL )

narrow your search

- Products
- Controls Monitoring and Lighting (352)
  - Machine Safety (1727)
  - Sensors (5901)
  - Switches (9775)
  - Wireless (39)

- Technology
- Control and Instrumentation (1052)
  - Electromechanical (9301)
  - Magnetic (541)
  - Microstructure (1492)
  - Thick Film (1409)



Actual product appearance may vary.

TL Series Toggle Switch, 1 pole, 3 position, Solder terminal, Standard Lever, Military Part Number MS27734-28

Sales & Service

Distributor Inventory

contacts

- Customer Service
- Technical Support
- Global Sales & Service
- View Site Demo
- Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

my links

- Login to iCOM
- Login to Rep/AD Portal
- Login to Digital University

News Center

HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING

HONEYWELL RELEASES UNLIMITED POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES

HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS

MICRO SWITCH Anniversary site

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

- Wireless Switches Offer Unlimited Benefit
- Basic Switches Are Not Created Equal
- Applying Precision Switches
- Sensors for Medical Devices
- New Ways to Measure Torque
- Choosing Safety Switches
- Specifying Hour Meters

Need help?

Click here to contact us

Overview Specs Documentation Application Notes

Product Specifications

Circuitry/Operating action

Keyway Momentary Position Opposite Keyway Position



Product Type	MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc, 0.5 A to 15 A at 0.5 Vdc to 28 Vdc, 0.5 A at 250 Vdc, 0.5 A to 10 A at 0.5 Vac to 7 Vac
Circuitry	SPST
Action	3 position
Mounting	Bushing 15/32 in
Termination	Solder
MIL Spec. Number	MS27734-28
Lever Type	Standard
UL/CSA	L192: 10 A-125, 250, 277 Vac; 1/4 Hp-125 Vac; 1/2 Hp-250, 277 Vac; 3 A-125 Vac "L"
Comment	Single turret solder lug termination
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TL