




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

### 102TL2263-7



Actual product appearance may vary.

**TL Series Toggle Switch, 2 pole, 3 position, IWTS (16-20 Gage) terminal, No Lever**

#### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### Features

Environmentproof sealing  
 1,2, and 4 pole circuitry  
 Standard and pull-to-unlock levers  
 2 and 3 position, maintained and momentary toggle action  
 Temperature range: -85° F to +160° F  
 Completely sealed switching chamber  
 Step-design case provides added space between terminals to help prevent shorting  
 UL recognized, CSA certified  
 CE approved

#### Potential Applications

Industrial machinery and equipment  
 Military and commercial aviation  
 Construction equipment  
 Test instruments  
 Agricultural machinery  
 Process control  
 Medical instrumentation

#### Description

MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

#### Supporting Documentation

- [Accessory: Lever Sleeve](#)
- [Accessory: Seals](#)
- [Accessory: Nuts](#)
- [Engineering Drawing](#)

#### Keyword Search

Search for product and support information.

All Sensing and Control

#### Product Search

Part number search:

Use (\*) to expand search

#### Specification Search

Product Specifications			
Circuitry/Operating action	<b>Keyway</b>	<b>Center</b>	<b>Opposite</b>
	<b>Momentary Position</b>	<b>Position</b>	<b>Momentary Position</b>
	<b>ON</b>	<b>OFF</b>	<b>ON</b>
Product Type	MICRO SWITCH™ Toggle Switch		
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc, 0.5 A to 7.5 A at 0.5 Vdc to 28 Vdc, 0.5 A to 6 A at 0.5 Vac to 230 Vac, 0.5 A at 250 Vdc		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	IWTS (16 -20 Gage)		
Lever Type	No Lever		
Comment	100% immersion test per QS 047 287		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	TL		