



LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
AF	-		A2	REVISED PER ECR-16-017699	10JAN2017	JJ	DZ	

1. USE WITH VAL-U-LOK HOUSINGS.
2. FOR USE WITH #22-#18 AWG LEAD WIRE WITH INSULATION DIA 2.16-2.79MM AND INSULATION CRIMP HEIGHT OF 3.05 MIN.
3. SIDE LATCHES ONLY, NO TOP LATCHES FOR POSITIONS 1-5



1969608-7 SHOWN HERE

53.94	53.90	55.60	12	1-1969608-2
49.74	49.70	51.40	11	1-1969608-1
45.54	45.50	47.20	10	1-1969608-0
41.34	41.30	43.00	9	1969608-9
37.14	37.10	38.80	8	1969608-8
32.94	32.90	34.60	7	1969608-7
28.74	28.70	30.40	6	1969608-6
24.54	24.50	26.20	5	1969608-5 3
20.34	20.30	22.00	4	1969608-4 3
16.14	16.10	17.80	3	1969608-3 3
11.94	11.90	13.60	2	1969608-2 3
7.74	7.70	9.40	1	1969608-1 3
DIM S	DIM R	DIM L	# OF POS	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. EDWARDS 08JAN2013	TE Connectivity	
DIMENSIONS:		CHK JR RUTH 03JUN13		
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD KURT RANDOLPH 04JUN13	NAME	
	0 PLC ±.3	PRODUCT SPEC	HOUSING, TPA, VAL-U-LOK	
	1 PLC ±0.3	APPLICATION SPEC		
	2 PLC ±0.10		SIZE	CAGE CODE
	3 PLC ±0.001		A1	00779
	4 PLC ±0.0001		DRAWING NO	
	ANGLES ±.0001		C=1969608	
MATERIAL	FINISH	WEIGHT	RESTRICTED TO	
NYLON 6/6	COLOR: BLACK	-	-	
		Customer Drawing	SCALE	8:1
			SHEET	1
			OF	1
			REV	A2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1969608-7](#)