

Seal - WR-DA-M40 - 1644876

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Seal, outside, to increase the degree of protection, size M40

The illustration shows the version WR-DI-PG 21 and WR-DA-PG21



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	5 STK
GTIN	4 017918 911157
GTIN	4017918911157
Weight per Piece (excluding packing)	12.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General


Seal material	PUR

Drawings



Seal - WR-DA-M40 - 1644876

Dimensional drawing



Assembly instructions for M40 corrugated pipe

- a = Corrugated screw connection
- b = Corrugated pipe
- c = Opener

Installation note:

Cut the corrugated pipe in the groove to retain a round shape for insertion. The lighter seal (not depicted in the illustration) is positioned in the corrugated pipe screw connection below the safety latch. The darker outer seal (not depicted in the illustration) is placed over the corrugated pipe screw connection from outside. The corrugated pipe is then pushed as far as possible into the corrugated pipe screw connection and clicks into place. The screw connection is opened by placing the yellow corrugated pipe opener with force between the safety latch and the corrugated tube and the corrugated pipe is then pulled out.

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27439218
eCl@ss 9.0	27430319

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC002498
ETIM 5.0	EC001181
ETIM 6.0	EC001181

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408



Seal - WR-DA-M40 - 1644876

Classifications

UNSPSC

UNSPSC 12.01	39121408
UNSPSC 13.2	39131608

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com