

W-Series
WPDB 35/16/6/N 1/2/5/11

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The versatile and extensive range of products - from 0.05 mm² to 300 mm² - means that you have diverse options for your applications at your disposal. Hardened steel for mechanical strength and high-quality tinned copper for optimum conductivity. All materials comply with RoHS requirements and have been tested to current environment guidelines.

General ordering data

Type	WPDB 35/16/6/N 1/2/5/11
Order No.	1939510000
Version	W-Series, Distribution block, Rated cross-section: 0 mm ² , Screw connection
GTIN (EAN)	4032248615896
Qty.	1 pc(s).

W-Series
WPDB 35/16/6/N 1/2/5/11

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	74 mm	Width	98 mm
Height of lowest version	45 mm	Weight	314 g
Net weight	313.4 g		

Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

Additional technical data

Explosion-tested version	No	Open sides	closed
Type of mounting	Snap-on	Version	Screw connection, closed

Clampable wires (additional connection)

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, min.	6 mm ²	Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.	35 mm ²
---	-------------------	---	--------------------

Clampable wires (rated connection)

Type of connection	Screw connection	Connection direction	on side
Wire connection cross section, solid core, max. rated connection	6 mm ²	Wire connection cross section, solid core max. rated connection	35 mm ²
Wire connection cross section, finely stranded, max.	35 mm ²	Wire connection cross-section, finely stranded, min.	6 mm ²
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.	6 mm ²	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.	35 mm ²

Rated data

Rated cross-section	0 mm ²	Rated voltage	690 V
Rated impulse withstand voltage	8 kV	Rated current	125 A
Current at maximum wires	125 A	Standards	IEC 60947-7-1
Pollution severity	3		

UL ratings data

Certificate No. (cURus)	E223821AUXEL
-------------------------	--------------

Material data

Material	Wemid	Colour	Dark Beige
UL 94 flammability rating	V-0		

System specifications

Product family	W-Series	Type of connection	Screw connection
Connection direction	on side	Number of levels	3
Levels cross-connected internally	Yes	Mounting rail	TS 35
End cover plate required	No		

Data sheet...

W-Series
WPDB 35/16/6/N 1/2/5/11

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

ETIM 3.0	EC000897	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-20	eClass 6.2	27-14-11-20
eClass 7.1	27-14-11-20		

Product information

Descriptive text technical data	1500 V DC
---------------------------------	-----------

Approvals

Approvals



ROHS	Conform
------	---------