




LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION		DATE	DWN	APVD
	D1	REVISED PER ECO-11-005027		11MAR11	RK	HMR

NOTES:



PHYSICAL PROPERTIES:  
HOUSING: THERMOPLASTIC, UL94V-0, BLACK.  
TERMINALS: BRIGHT TIN OVER COPPER ALLOY.  
SCREWS: #6-32 STEEL, ZINC PLATING W/ CLEAR CHROMATE.  
  
PITCH: .375"  
OPERATING TEMP: 105°C  
RECOMMENDED TIGHTENING TORQUE: 7 IN-LBS.

ELECTRICAL PROPERTIES  
CURRENT RATING: 20A.  
OPERATING VOLTAGE: 300V.  
WIRE RANGE: 12-22 AWG.



MOUNTING PANEL LAYOUT

7.439	7.125	18	BC6-Q308-18	1-1546781-1
7.064	6.750	17	BC6-Q308-17	1-1546781-0
6.689	6.375	16	BC6-Q308-16	1546781-9
6.314	6.000	15	BC6-Q308-15	3-1437662-1
5.939	5.625	14	BC6-Q308-14	1546781-8
5.564	5.250	13	BC6-Q308-13	3-1437662-0
5.189	4.875	12	BC6-Q308-12	1546781-7
4.814	4.500	11	BC6-Q308-11	1546781-6
4.439	4.125	10	BC6-Q308-10	2-1437662-9
4.064	3.750	9	BC6-Q308-09	1546781-5
3.689	3.375	8	BC6-Q308-08	1546781-4
3.314	3.000	7	BC6-Q308-07	1546781-3
2.939	2.625	6	BC6-Q308-06	2-1437662-8
2.564	2.250	5	BC6-Q308-05	1546781-2
2.189	1.875	4	BC6-Q308-04	1546781-1
1.814	1.500	3	BC6-Q308-03	2-1437662-4
1.439	1.125	2	BC6-Q308-02	2-1437662-3
DIM. A	DIM. B	NO. OF POS.	CATALOG NUMBER	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. SCHLEGEL 9/15/03	 TE Connectivity				
		CHK S. YODER 9/15/03					
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD S. YODER 9/15/03	NAME  BC6-Q308-XX ASSEMBLY				
	0 PLC ± -	PRODUCT SPEC					
	1 PLC ± -	-					
	2 PLC ± .01	APPLICATION SPEC					
	3 PLC ± .005	-					
4 PLC ± -	WEIGHT -	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
ANGLES ± -		A3	00779	C-2-1437662-3			
MATERIAL -	FINISH -	CUSTOMER DRAWING			SCALE NTS	SHEET 1 OF 1	REV D1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1546781-4](#)